

3", 4", 5" and 6" targeted LED downlighting with a twist

The LED iGimbal downlighting modules are **adjustable and easy to install** for retrofit and new construction applications, these fixtures offer more lumens to brighten your space for 35,000 hours, with dimmable capabilities to create the perfect ambiance for directional lighting and wall washing. **The iGimbal is now offered in a 3" aperture, as well as the traditional industry 4", 5", and 6" apertures.** By replacing your incandescent downlighting with the new LED iGimbals, you can **save 80% in energy costs with a fixture that's virtually maintenance free.**

Key Features:

- Over 50° of up/down adjustable tilt with 360° of rotation
- Replaces 50W and 65W general purpose flood
- Available in 2700K, 3000K and 4000K color temperatures
- Combines functionality of an "eyeball" with ease of using a gimbal
- 90CRI Standard
- 24/7 "Commercial Grade"



Learn more about the LED iGIMBALS at www.lithonia.com

LED iGIMBALS



3" LED iGimbal:

Lumen output	Replaces up to	Watts
560	50W incandescent	8.7

4" LED iGimbal:

Lumen output	Replaces up to	Watts
640	50W incandescent	9.8

5" LED iGimbal:

Lumen output	Replaces up to	Watts
750	65W incandescent	12.2

6" LED iGimbal:

Lumen output	Replaces up to	Watts
750	65W incandescent	12.2

Ordering Information

EXAMPLE:	4iGMW	LED	30K 90CRI

LED	LED IGIMBALS			
Ser	ies	Finish	Lamp	CCT/CRI
3iG	3" iGimbal Module	MW Matte White MB¹ Matte Black BN¹ Brush Nickel ORB¹ Oil-rubbed-Bronze	LED	27K 90CRI 2700K/90 CRI 30K 90CRI 3000K/90 CRI 40K 90CRI 4000K/90 CRI
4iG	4" iGimbal Module			
5iG	5" iGimbal Module			
6iG	6" iGimbal Module			

Included Items:



¹ Minimum 90-day lead time for non-standard color finishes and 4000K; minimum 50 order quantity.

















