


YOU DESERVE



Date:	Project:
Prepared for:	Type:
Comments:	

WALL PACK 11

FEATURES & SPECIFICATIONS

Electrical Characteristics	<ul style="list-style-type: none"> • Input Voltage: 120-347Vac • Rated Power between: 21W/28W/35W 45W/60W/75W
Colour Temperature	• 3CCT Selectable (3000K/4000K / 5000K)
Wire size of leads	• 18 AWG
Length of leads	• 18"
Colour Rendering Index	• +80
Lumen Output	<ul style="list-style-type: none"> • 2730lm at 21W • 3640lm at 28W • 4550lm at 35W • 5850lm at 45W • 7800lm at 60W • 9750lm at 75W
Beam Spread	• Type 3
Tilt inclinasion	• 10 positions 0° to 90° degrees
Operating Temperatures	• -40°C to 45°C
Dimmable	• 0-10V
Environment	• IP65: Suitable for wet locations
Materials	<ul style="list-style-type: none"> • Die cast Aluminum Body • Polycarbonate Lens
Codes & Standards	<ul style="list-style-type: none"> • UL • DLC Premium 
Lifetime	• 50 000 hours
Warranty	• 5 years



*Photocell included

ORDERING INFORMATION

Series	Input Voltage	Colour Temperature	Equivalet Power	Rated Power	DLC Product ID	Ordering Code
WALL PACK 11	120-347Vac	SELECTABLE 3000K 4000K 5000K	100W	21W/28W/35W	S-UM891H	WP11-35W-VAR-V3
			250W	45W/60W/75W	S-QUX2ES	WP11-75W-VAR-V3

