

Date: _____ Project: _____
Prepared for: _____ Type: _____
Comments: _____

LED MINI FLOOD LIGHT

VERSION 4

IP66

LED MINI FLOOD LIGHTS
15W / 50W



Lifetime
50 000 hours



IP66
Suitable for use in wet locations



15W, 4000K
50W, 4000K, 5000K
ONLY



15W, 3000K
ONLY



E475776

SPECIFICATIONS

IP66 - Suitable for Wet Locations
Robust Die-Cast Aluminium Casing
UV-Resistant Poly-Carbonate Lens
Colour Rendering Index: >70
Functioning Temperature: -40°C to 45°C

AVAILABILITY

15W / 50W
3000K / 4000K / 5000K
100-277VAC
KNUCKLE / BRACKET



This is a STOCK item:

Look for our Same Day Shipping icon for all products that ship out on the same day (orders must be placed before 3pm EST)





Full ies File Available on Request

ORDERING INFORMATION



LED Mini Flood Light V4
(Knuckle-Mount)

LED Mini Flood Light V4
(Bracket-Mount)



ITEM	A	B	C	D	E	F	G
50W	9.0"	8.4"	2.2"	2.3"	9.8"	7.7"	2.6"
15W	5.1"	6.1"	3.3"	1.8"	5.7"	4.3"	1.5"

[K,Y] OR [S,K,Y]

K STANDS FOR KNUCKLE

Y STANDS FOR BRACKET

S STANDS FOR SLIP FITTER

[BLANK;(PTC)] OR [BLANK;PTC]

BLANK STANDS FOR NO PHOTOCELL

(PTC) OR PTC STANDS FOR PHOTOCELL

SERIES	POWER (WATTS)	EQUIVALENT TO (WATTS)	LUMENS	INPUT VOLTAGE	COLOR TEMP	MODEL NUMBER	MOUNTING OPTION	ORDERING CODE
MINI FLOOD LIGHT V4	15W	45W	1800	100-277VAC	3000K	FLO12R0015W-80X110-[K,Y]-30K	KNUCKLE	FL-15W-30K-K-V4
					BRACKET	FL-15W-30K-Y-V4		
	50W	150W	6000	100-277VAC	4000K	FLO12R0015W-80X110-[K,Y]-40K[BLANK;(PTC)]-V4	KNUCKLE	FL-15W-40K-K-V4
					BRACKET	FL-15W-40K-Y-V4		
					4000K	FLO12R0050W-80X110-[K,Y]-40K[BLANK;(PTC)]-V4	KNUCKLE	FL-50W-40K-K-V4
					BRACKET	FL-50W-40K-Y-V4		
5000K	FLO12R0050W-80X110-[K,Y]-50K[BLANK;(PTC)]-V4	KNUCKLE	FL-50W-50K-K-V4					
		BRACKET	FL-50W-50K-Y-V4					