

Date:	Project:
Prepared for:	Туре:

LED High Bay V2

100-347VAC

Rectangular Driver

U-Bracket Included

LED High Bay

HIGH BAY V2

IP65 | DIMMABLE



















DIMENSIONS

100W / 150W


Comments:


LED High Bay V2


100-277VAC

Round Driver

U-Bracket Not Included







SPECIFICATIONS

IP65 - Suitable for Wet Locations **External Driver for Easy Access Robust Aluminium Casing** Clear Polycarbonate Lens Beam Angle: 110° Colour Rendering Index: >70

Functioning Temperature: -40°c to 50°c

AVAILABILITY

100W / 150W / 200W 4000K / 5000K 100-277VAC / 100-347VAC

*This icon indicates a STOCK item: Look for this Same Day Shipping icon below in 'Ordering Information' for products that ship out on the same day (orders must be placed before 3pm EST)

ORDERING INFORMATION

SERIES	POWER (WATTS)	EQUIVALENT TO (WATTS)	LUMENS	COLOR TEMP	INPUT VOLTAGE	MODEL NUMBER	ORDERING CODE
LED HIGH BAY V2	100	200	13000	4000K	100-277VAC	HIG12R0100W-4000K-D-V2	HB-100W-40K-R-V2
				5000K	100-277VAC	HIG12R0100W-5000K-D-V2	HB-100W-50K-R-V2
	150	330	19500	4000K	100-277VAC	HIG12R0150W-4000K-D-V2	HB-150W-40K-R-V2
					100-347VAC	HIG12R0150W-4000K-DC-V2	HB-150W-40K-R-V2-347
				5000K	100-277VAC	HIG12R0150W-5000K-D-V2	HB-150W-50K-R-V2
					100-347VAC	HIG12R0150W-5000K-DC-V2	HB-150W-50K-R-V2-347 =
	200	400	26000	4000K	100-277VAC	HIG12R0200W-4000K-D-V2	HB-200W-40K-R-V2
					100-347VAC	HIG12R0200W-4000K-DC-V2	HB-200W-40K-R-V2-347
				5000K	100-277VAC	HIG12R0200W-5000K-D-V2	HB-200W-50K-R-V2
					100-347VAC	HIG12R0200W-5000K-DC-V2	HB-200W-50K-R-V2-347



Date:	Project:
Prepared for:	Туре:
Comments:	



NOTABLE ARANI PROJECTS











