


Connect (push) electrical wires from fixture into correct inserts.


STYLE#2

Bracket

Black (live), White (neutral), Green (ground)



## CONNECT LIGHT FIXTURE **STEP 3**



Fixture

Stud

Nipple

Cap

Nut

evenly.

Or


 $\subset$ 

STEP 4 STYLE#1

Star

Washer

Connect (push) electrical wires from electric box (house wiring) into correct inserts. Black (Live), White (Neutral), Green (Ground)



Black (Live)

For multiple black (live) & white (neutral) wires joined in the electrical box (house wiring), attach a single "black" and "white" Jumper Wire before connecting. Strip 7mm from a 6" Jumper Wires (AWG 12-24) supplied. Then connect (push) wires into correct inserts.

STEP 5 - Note: Refer to the style of assembly that matches the style of your fixture.

STYLE#1- Tuck electrical wires into

outlet box and position fixture over


star washer(s) and cap nut(s).

studs or nipple on mounting bracket


assembly. Secure fixture in place with

Note: If required, assemble body and

spread the arms of the fixture out



**STYLE#1** - Secure the centre stem onto the screw stud. Install the proper bulb type and wattage . Secure the glass in place using the decorative cap, hex nut, fibre washer and finial.



Fixture

Screw

**STYLE #2** - Insert one screw into the mounting bracket - do not tighten yet. Tuck electrical wires into outlet box and position fixture over the mounting bracket. Line up the screw in the bracket to the "7" hole on the fixture. Slide fixture to secure in place. Insert remaining screw. Tighten both screws to secure.

**STYLE#2** -Secure the centre stem onto the screw stud. Install the proper bulb type and wattage . Secure the glass in place by the finial.

Imported By: CANARM LTD., 2157 Parkedale Ave., Brockville, Ontario, K6V 5V6, Tel: (613) 342-5424, Fax: (800) 263-4598