



CONNECT HOUSE WIRES **STEP 2 - Option 1**




CONNECT LIGHT FIXTURE STEP 3



Connect (push) electrical wires from fixture into correct inserts. Black (live), White (neutral), Green (ground)

STEP 4




STYLE#1- Tuck electrical wires into outlet box and position fixture over studs or nipple on mounting bracket assembly. Secure fixture in place with star washer(s) and cap nut(s). **Note:** If required, assemble body and spread the arms of the fixture out evenly.

inserts. Black (Live),


White (Neutral),

Green (Ground)




STYLE #2 - Insert one screw into the mounting bracket - do not tighten yet. Tuck electrical wires into outlet box and position fixture over the mounting bracket. Line up the screw in the bracket to the "7" hole on the fixture. Slide fixture to secure in place. Insert remaining screw. Tighten both screws to secure.

STEP 5 - Note: Refer to the style of assembly that matches the style of your fixture.



Spread the arms evenly. Attach the stem to the fixture and position the glass over the stem. Secure the glass in place using the fibre washer, hex nut, decorative cap and finial. Install proper bulb type and wattage.

Connect (push) electrical wires from electric box (house wiring) into correct



For multiple black (live) & white (neutral) wires joined in the electrical box (house wiring), attach a single "black" and "white" Jumper Wire before connecting. Strip 7mm from a 6" Jumper Wires (AWG 12-24) supplied. Then connect (push) wires into correct inserts.

Option 2 - MULTIPLE ELECTRICAL BOX WIRES