


CONNECT LIGHT FIXTURE **STEP 3**



Black (Li

Black (live), White (neutral), Green (ground)


Connect (push) electrical wires from fixture into correct inserts.

(house wiring) into correct

inserts. Black (Live),


White (Neutral),

Green (Ground)




For multiple black (live) & white (neutral) wires joined in the electrical box (house wiring), attach a single "black" and "white" Jumper Wire before connecting. Strip 7mm from a 6" Jumper Wires (AWG 12-24) supplied. Then connect (push) wires into correct inserts.

STEP 4




Tuck electrical wires into outlet box and position fixture over studs or nipple on mounting bracket assembly. Secure fixture in place with star washer(s) and cap nut(s). **Note:** If required, assemble body and spread the arms of the fixture out evenly.

STEP 5 - Optional for some models (Note: Refer to the style of assembly that matches the style of your fixture.)



STYLE#1 - Remove spinner nut from socket. Position glass on the fixture and secure with spinner nut. Install proper bulb type and wattage.

Note: Glass may face up or down.



STYLE#2 - Install proper bulb type and wattage. Install the glass to the fixture by tightening the 2 thumb screws.

Imported By: CANARM LTD., 2157 Parkedale Ave., Brockville, Ontario, K6V 5V6, Tel: (613) 342-5424, Fax: (800) 263-4598