IVL670A 09/16

EASY CONNECT® INSTALLATION INSTRUCTIONS

OUESTIONS OR CONCERNS CONTACT AT:

1-800-265-1833 (English) / 1-800-567-2513 (French) Monday through Friday 8:00 AM to 5:00 PM E.S.T.




INSTRUCTIONS PERTAINING TO RISK OF FIRE OR INJURY TO PERSONS **READ ALL INSTRUCTIONS**

IMPORTANT SAFETY INSTRUCTIONS SAVE THESE INSTRUCTIONS

SAFETY PRECAUTIONS:

- 1. TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.
- 2. WIRING SUPPLIES AS REQUIRED BY LOCAL ELECTRICAL CODE.
- 3. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.
- 4. TO CLEAN THE FIXTURE, TURN OFF THE POWER, WAIT FOR IT TO COOL, AND WIPE THE FIXTURE WITH A CLEAN, SOFT CLOTH.
- NOTE: Product may not look exactly as shown in figures.

INSTALLATION:



(Ground)

⊕


Green (Ground)

screws

Option 1


White (Neutral)

- $\mathbb{1}_{\circ}$ Attach nipple to mounting bracket. Adjust so it will clear hole in back of fixture and then lock nipple in place with hex nut.
- 2 Attach mounting bracket to electrical box with electrical box screws (not included).
- 3. Option 1: Connect (push) electrical wires from electric box (house wiring) into correct inserts.
- Option 2: For multiple black (live) & white (neutral) wires joined in the electrical box (house wiring), attach a single "black" and "white" Jumper Wire before connecting. Strip 7mm from a 6" Jumper Wires (AWG 12-24) supplied. Then connect (push) wires into





cap nut.



4. Connect (push) electrical

wires from fixture into correct

5. Once connections of

wires are completed, carefully

tuck wires and wire nuts into

the electrical box making sure

no bare wire (on the black and


white) is visible at the wire

over nipple and secure in

place with star washer and

nuts. Position hole in fixture

inserts.



Bulb

