

LED

4" Recessed Downlight

DL-4-9YC-BN-C

CANARM LTD.

 PO Box 367, 2157 Parkedale Avenue, Brockville, Ontario K6V5V6
 Tel: 613-342-5424 | Fax: 1-800-263-4598

 2555 Rue Bernard Lefebvre, Laval, Quebec H7C 0A5
 Tel: 1-450-665-2535 | Fax: 1-450-665-0910

 808 Commerce Park Drive, Ogdensburg, New York, USA 13669
 Tel: 1-800-267-4427 | Fax: 1-800-263-4598

www.canarm.com
General

Size of Fixture: 5.12" W x 5.12" H x 2.09" D
 Finish: brushed nickel
 Gimbal trim, Acrylic lens
 IC Rated, Driverless, 120 Volt, 9W
 Lumens: 500 lumens thru the lens, Dimmable
 Beam spread: 120°
 Bulb Life: 50,000 hours
 CRI: 90
 Colour Temperature: 3000K
 Starting Minimum Temperature: -40°C
 Compatible dimmers: LEVITON #742-6672-HLW,
 LEVITON #722-6674-PDW, LUTRON #SCL-153PH-WH
 Recessed mounted, J-Box included
 Max.# of lamps per 150W dimmer: 16 pcs
 Cut-out template: 4 3/8"


Packaging

Colour Box: 6.65" x 5.39" x 2.83" (169 x 137 x 72mm)
 Colour box weight: 0.70 lbs
 Master box: 13.98" x 11.61" x 15.16" (355 x 295 x 385mm)
 Pieces per Master box: 20
 Master box weight: 15.61 lbs

Warranty & Safety Standards

Warranty: LED Module-Limited 5 year
 Fixture-Limited 1 year
 cETLus rated
 Energy Star Rated
 Suitable for wet locations
 Indoor/Outdoor enclosed use

Prepared for
Contact
Date
Presented by
Remarks