

# Mini Flood Light





Ideal for landscaping, patio, and security lighting, signs, and building facades

Excellent replacement for quartz halogen fixtures

# High-Impact Polycarbonate Lens/Optics Die-Cast Aluminum Housing with cooling fins for superior heat dissipation Knuckle Mount Rugged Polyester Powder Coat Finish (Bronze) 0.5m Power Cord 1/2" NPT for precise aiming

Suggested Substitutions: FLM-15W-40K-LV-YK



# **TECHNICAL DATA**




## LIGHT SPECIFICATIONS

Lumens	1,603 lm
Efficacy	111.05 lm/W
CCT	4000K
CRI	80
L70 Life	50,000 hrs
Warranty	10-year

# APPROVALS AND LISTINGS

cUL	E482965
DLC	PL32CM5XTF57

### **DIMENSIONS**



# **ISOCANDELA**



### **ELECTRICAL**

Wattage	15W
Voltage	120-277V
Power Factor	0.9
THD	18.39%
Operating Temp	-40 to 50°C

### CONSTRUCTION

Housing	Aluminum Alloy	
Finish Bronze		
IP Rating	IP65	
Carton Weight	10.4 kg	
Carton Qty	8	
Carton Dimensions	484 x 302 x 297 mm	

### SUGGESTED SUBSTITUTION

FLM-15W-40K-LV-YK

# **ILLUMINANCE AT A DISTANCE**

Illuminance at a Distance						
	Center Beam fc	Beam Width				
17.0 <del>R</del>	2.07 fc	50.5 ft	45.1 ft			
34.0 <del>R</del>	0.52 fc	101.1 ft	90.2 ft			
51.0 <del>R</del>	0.23 fc	151.6 ft				
68.0 <del>R</del>	0.13 fc	202.2 ft	180.4 ft			
85.0 <del>R</del>	0.08 fc		225.6 ft			
102.0R	0.06 fc	303.3 ft	270.7 It			
■ Vert. Spread: 112.1° ■ Horiz. Spread: 106.0°						

Western Canada Warehouse: 121-1647 Broadway Street, Port Coquitlam, BC V3C 6P8 | ordersbc@csc-led.com

