

Rotatable Wall Pack

40W | 5000K | 120-277V



Ideal for security lighting, wall washing, flood lighting, and more
Use as an uplight, downlight, or flood light

Heavy Die Cast Aluminum

LM80 Tested
CREE Chips

Flexible Light Control



270° Rotatable Module

Superior Anodized
Paint Finish

Oversized Heat Sink
for Superior Thermal
Management



TECHNICAL DATA




LIGHT SPECIFICATIONS

Lumens	5,131 lm
Efficacy	128.18 lm/W
CCT	5000K
Beam angle	60°
CRI	73.5
Dimmable	No
Rated hours	50,000
Warranty	10-year

APPROVALS AND LISTINGS

cUL	E482965
DLC	PL3VERZYMHTN

ILLUMINANCE CONE



ELECTRICAL

Wattage	40W
Voltage	120-277V
Power factor	0.91
THD	18.95%
Operating temp	-30° to 45° C

CONSTRUCTION

Housing	Cast aluminum
Finish	Anodized finish
Colour	Black
IP Rating	IP65
Weight	4.07 lbs
Carton qty	4

ACCESSORIES (SOLD SEPARATELY)

RWP-EXT-PLATE	Extension Plate
---------------	-----------------



DIMENSIONS

