

# Assembly Instruction Sheet #S-1125C16-4 For Style 1125C16-4

**Tools Required:** Padded screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.  
**Light Source:** (4) SUCCENTED LED G9 BALL BULB (Not Included).  
**Estimated Assembly Time:** 20-30 minutes  
**Preparation:** Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

**⚠ Warnings and Cautions**  
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

## Package Contents

- [B]** Glass Shade x4
- [A]** Fixture Body x1

PART NUMBER	DESCRIPTION	QUANTITY
AA	Screw	2
AB	Shielded Leads	2
CC	Outlet Box	1
DD	Mounting Screw	2
EE	Crossbar	1
EE	Canopy	1




Figure 1



Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

