



Thinline 3.18

Wall Mount Wet Rated

delviro energy

94 Brockport Drive, Toronto, Ontario, M9W 7J8 | Tel. 1.877.502.3434 | info@delviro.com

www.delviro.com



Thinline 3.18

Wall Mount Wet Rated

FEATURES

- Aluminum housing 3.18" wide
- Lengths: 2', 4', 6', 8'
- Polycarbonate frosted lens
- Louver lens option
- Wall wash optic option
- Wet locations rated
- Motion sensor compatible
- Standard Grey, White and Black finishes
- Custom finishes available



10 Year
Warranty

SPECIFICATIONS

Efficacy:

98 Lm/W

CRI:

80+

Color Temperature:

3000K, 3500K, 4000K, 5000K

Lumen Maintenance:

200,000+ Life Hours (L70)

Voltage:

120/277V | 347V | 480V (option)

Control Options:

0-10V Dimming, DMX, DALI, Wireless

Operating Temperature:

-20°C to +40°C

Mounting Options:

Wall Mount

Wiring Options:

Black, White, Grey Flexible Cord,
3 and 5 Conductor Wire

Accessories:

10kV Surge Protection,
0-10 1% Dim to Off Driver

OUTPUT PERFORMANCE

Watts/ft	Delivered Lumens/ft
2.5	250
3.5	350
5	500
7.5	750
10	1000

Custom Output Packages

Step 1:

Select Model:

2', 4', 6', 8'

Step 2:

Select:

Watts/ft - Delivered lumens/ft

Sample Output Package: Thinline 8', 10W/ft - 1000 Delivered lumens/ft

yields: 80W and 8000 Lumens

** Watts per foot available on all lengths*

MAX LINEAR FT

Model	Feet
120V	120
240V	240
277V	250
347V	250

Note: Not all products are qualified on the DLC QPL.

To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.



delviro energy

94 Brockport Drive, Toronto, Ontario, M9W 7J8 | Tel. 1.877.502.3434 | info@delviro.com | www.delviro.com

© delviro energy 2018

Specifications subject to change without notice.



DIMENSIONS



Note: End Cap Length: .09" | 2 End Caps add additional .180" in length


WALL MOUNT INSTALLATION

1. Using the assembled unit (as shipped), mark the position of the wall brackets so you make sure brackets are properly aligned.
2. Wall marks should be **Length - 4.25"** (Table) apart as shown on diagram A.
3. Remove locking screws from both brackets and keep.
4. Using the wall mount bracket mark the position of the mounting holes from inside the bracket.
5. Attach brackets to wall (screws not supplied) using 1/4" screws.
6. Slide the unit mount brackets (factory assembled) into the wall bracket.
7. Reattach the locking screws on the top and bottom (from Step 3).



TABLE

Model	Wall Mounting Length
Thinline 2'	19.75"
Thinline 4'	43.75"
Thinline 6'	67.75"
Thinline 8'	91.75"




delviro energy

94 Brockport Drive, Toronto, Ontario, M9W 7J8 | Tel. 1.877.502.3434 | info@delviro.com | www.delviro.com

© delviro energy 2018

Specifications subject to change without notice.


FINISH OPTIONS




GREY
Standard Finish




WHITE
Standard Finish




BLACK
Standard Finish




ORANGE
Custom Finish



RED
Custom Finish



BLUE
Custom Finish



GOLD
Custom Finish

ADDITIONAL FINISHES AVAILABLE
Please contact delviro.com for more information

ORDERING GUIDE

MODEL	WATTS/ft	COLOR TEMP	VOLTAGE	LENS	FINISH	MOUNTING
DTL2	2.5	3K 3000K	U 120/277V	FR Frosted	GRY Grey	WM Wall Mount
DTL4	3.5	35K 3500K	H 347V	LV Louver	WH White	
DTL6	5	4K 4000K	480V		BLK Black	
DTL8	7.5	5K 5000K			CU Custom	
	10					

						WM
--	--	--	--	--	--	-----------

WIDTH	WIRING	ACCESSORIES	TYPE
3.18 3.18"	BFC Black Flexible Cord WFC White Flexible Cord GFC Grey Flexible Cord 3 WIRE 3 Conductor Wire ___ 5 WIRE 5 Conductor Wire ___ N No Cord	N None WC Wireless Controls DMX DALI 10kV 10kV Surge Protection DIMOFF 0-10 1% Dim to off Driver	WMWR Wall Mount Wet Rated WWRW Wall Mount Wet Rated Wall Wash

3.18			
-------------	--	--	--

NOTE

480V - Please consult factory
LV - Please consult factory
CU - Please consult factory