

Date:	Fixture:
Qty:	Client/ Project:



Titan HB C

High Bay

FEATURES

- Aluminum construction
- Polycarbonate protective lens
- Dry and Damp Rated
- Driver accessible drawer
- Natatorium option



10 Year
Warranty

SPECIFICATIONS

Efficacy:

Up to 154 Lm/W

CRI:

86

Color Temperature:

3000K, 3500K, 4000K, 5000K

Lumen Maintenance:

200,000+ Life Hours (L70)

Watts:

80W, 120W, 160W, 240W,
320W, 480W

Voltage:

120/277V | 347/480V

Control Options:

0-10V Dimming, WIFI, Occupancy
Sensor, Bi-Level Dimming

Operating Temperature:

-25°C to +40°C
-25°C to +55°C - Option Available

Mounting Options:

V Hook, Jack Chain, Aircraft Cable,
Mounting Stem, Diecast Mounting Plate,
Indirect-Uplight Mounting Bracket

Wiring Options:

Black Flexible Cord
White Flexible Cord

Accessories:

10kV Surge Protection

OUTPUT PERFORMANCE

Model	Watts	Lm/W	Delivered Lumens
TitanHB 80c	75.8	144	11057
TitanHB 120c	111.7	153	17312
TitanHB 160c	156	146	22725
TitanHB 240c	223	149	33346
TitanHB 320c	296	148	43595
TitanHB 480c	444	154	68620

Note: Not all products are qualified on the DLC QPL.

To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.




delviro energy

94 Brockport Drive, Toronto, Ontario, M9W 7J8 | Tel. 1.877.502.3434 | info@delviro.com | www.delviro.com

© delviro energy 2018

Specifications subject to change without notice.

DIMENSIONS



MODELS	Nominal Length A	Width B	Width C
Titan HB 80	24"	6.654"	
Titan HB 120	36"	6.654"	
Titan HB 160	47.5"	6.654"	
Titan HB 240	36"		12.60"
Titan HB 320	47.5"		12.60"
Titan HB 480	47.5"		27.22"

ORDERING GUIDE

MODEL	WATTS	COLOR TEMP	VOLTAGE	LENS	FINISH	MOUNTING
TitanHB	C80	3K 3000K	U 120/277V	FR Frosted	WH White	V V Hook
	C120	35K 3500K	H 347/480V	CL Clear	CU Custom	JC72 Jack Chain Set 4 X 72" w/ "S" hooks included
	C160	4K 4000K		CLG Clear Glass		JC96 Jack Chain Set 4 X 96" w/ "S" hooks included
	C240	5K 5000K				JC144 Jack Chain Set 4 X 144" w/ "S" hooks included
	C320					ACY120 Aircraft Cable 120" W/Y Toggles & Adjusters
	C480					ACY200 Aircraft Cable 200" W/Y Toggles & Adjusters
TITANHB						

MOUNTING	WIRING	ACCESSORIES	PLUG
MS3-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 3' threaded at both ends	BFC Black Flexible Cord WFC White Flexible Cord	N None OCC Occupancy Sensor (on/off) WC Wireless Controls* BLD Bi Level Dimming (100%/10%) GCC Gasketed and Conformal Coated DA Dimming Wire Accessible 10kV 10kV Surge Protection	N None *See Plug Options
MS4-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 4' threaded at both ends			
MS6-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 6' threaded at both ends			
MS8-1/2W Mounting Stem 1/2" IPS (7/8" O.D.) 8' threaded at both ends			
1/2 NPT Diecast Mounting Plate with 1/2" NPT			
3/4 NPT Diecast Mounting Plate with 3/4" NPT			
IND Indirect-Uplight mounting bracket			
TG T Grid (Kit)			

NOTE

TG - See TitanHB 80 and TitanHB 160 with recessed kit specification sheet or consult factory
TitanHB Natatorium - includes conformal coated boards and gasketing for damp and chlorine rated environments.
WC - Please consult factory

PLUG OPTIONS

5-15P - 125V 15A T-Slot Plug	6-20P - 250V AC 20A Plug	24-20P - 347V AV 20A 3W/2P Plug NEMA 24-20
L5-15P - 125V 15A Locking Plug	L6-20P - 250V 20A Locking Plug	L24-20P - 347V 20A Locking Plug
5-20P - 125V AC 20A T-Slot Plug	7-15P - 277V 15A 3W/2P NEMA 7-15 Plug	24-15P - 347V AC 15A 3W/2 Plug NEMA 24-15
L5-20P - 125V 20A Locking Plug	L7-15P - 277V 15A Locking Plug	
6-15P - 250V AC 15A 3W/2P Plug NEMA 6-15	7-20P - 277V AC 20A Plug	
L6-15P - 250V 15A Locking Plug	L7-20P - 277V 20A Locking Plug	