SPECIFICATION SHEET										
SUBJECT										
6" LED DISK LIGHT SURFACE MOUNT										
CUSTOMER PROJECT										
Project:										
Type:										
Cat. No.:										
Qty:										
Date:										
EEL Rep:										





Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

# **DESCRIPTION**

The LED Disk Light Surface Mount fixture is dimmable and features a painted white finish on a high quality aluminum housing and a frosted PC diffuser. The DOB (driver on board) design enables it to be perfect for both commercial and residential applications. Ideal for entrances, living rooms, bedrooms, kitchens, dens, bathrooms and locations under a porch or eave.



# **SPECIFICATION FEATURES**

# Construction

Flush mount high quality aluminum housing painted white, frosted PC lens

1 size: 6-inch

#### Control

Driver is built inside the fixture. DOB (driver on board) design.

#### **Electrical**

Long Life LED System complete with electrical driver (DOB design) to deliver the optimal performance LED's available in both 3000K and 4000K with a typical CRI: 80

Ambient temperature -40°C to 42°C Electronic drivers are available in 120 Volt triac dimmable applications

LED modules rated for 50,000 hours.

# Mounting

Surface Mount

#### Finish

Painted white high quality aluminum

#### Shielding


The frosted PC diffuser provide a soft but effective distribution of light

### Compliance

Suitable for wet locations; cETLus and Energy Star

## Warranty

5 years



DL-LED-6-900-15 Dimension mm | 190.48(OD) x 112.5(ID) x 28(H) inch | 7.49"(OD) x 4.42"(ID) x 1.1"(H)



LED DISK LIGHT SURFACE MOUNT 6"







Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

# ORDERING CODE, ENERGY AND PERFORMANCE DATA

Model No.	Delivered Lumens (Im)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	Efficacy (Im/W)	Certification	Туре
DL-LED-6-900-15-3000K	900	15	120	3000K	60	C US DANGE TO MAKE	Standard
DL-LED-6-900-15-4000K	920	15	120	4000K	61	US PRIMITION	Standard

NOTE:
• Lumens are estimated