SUBJECT	SPECIFICATION SHEET							
Discus Rudi								
CUSTOMER PROJECT								
Project:								
Type:								
Cat. No.:								
Qty:								
Date:								
EEL Rep:								



# **Discus Rudi**

# **DISCUS SERIES**

Wattage(s)	10W, 15W					
Voltage	120-277V					
Dimmable	5.5" - Triac Dimmable 7" - 0-10V Dimmable					
сст	3000K, 4000K					
CRI	90					
Lumen Maintenance	L70 = 50,000h					
Operating Temperature	-30°C to 40°C					
Beam Angle	120°					



Power Factor >0.9



Telephone: 905 415 8878 Fax Number: 905 415 8872 Toll Free Telephone: 855 415 8878 Toll Free Fax: 855 415 8872

#### **DESCRIPTION**

The Discus Rudi is an ultra low-profile surface mounting luminaire with a modern and elegant look. High performance designed for easy installation. Suitable for residential or commercial installations.

### SPECIFICATION FEATURES

#### Construction

- · Matte white finishing, metal joint plastic housing
- Available in 5.5" & 7"

### Controls

- Driver is built inside the fixture
- DOB (driver on board) design

# Mounting

- Surface Mount
- Indoor ceiling or wall mounting
- Installation with recessed housing (5.5", 7") and junction box (For 5.5" fixture, a junction box with a minimum depth of 2 1/8 is suggested)

#### **Finish**

· Matte White

# Compliance

- cUL
- Energy Star
- FCC Rated
- IC / Airtight Rated
- Suitable for wet locations

#### Warranty

- 5-Year Warranty (Standard)
- 10-Year Limited Warranty (Optional)

# ORDERING CODE, ENERGY AND PERFORMANCE DATA

Model No.	Delivered Lumens (Im)	Input Watts (W)	Voltage (V)	Colour Temp. (K)	CRI	Efficacy (Im/W)	Certification
DR-R5314 Matte White 10W30K-120277V-Triac-CRI90	800	10W	120- 277V	3000K	90	80	C UL CONTROL
DR-R5334 Matte White 10W40K-120277V-Triac-CRI90	800	10W	120- 277V	4000K	90	80	C UL CONTROL
DR-R7514 Matte White 15W30K-120277V-010V-CRI90	1000	15W	120- 277V	3000K	90	67	c UL
DR-R7534 Matte White 15W40K-120277V-010V-CRI90	1000	15W	120- 277V	4000K	90	67	C UL CARRENT COM

NOTE:

Lumens are estimated

Ø7.15"

