



# CMP35/PAR30LN/SP



**Description** 35W PAR30 Long Neck Spot E26 Base 3000K 80+ CRI Ceramic Metal Halide

**Ordering Code** 06775

**UNSPSC Code** 39101614

## Specifications

<b>Watts</b>	35
<b>Base Type</b>	Medium Screw (E26)
<b>Bulb Type</b>	PAR30LN
<b>MOL in/mm</b>	4.92/125
<b>Mercury Content (mg)</b>	<3
<b>HG Form</b>	liquid
<b>Approx Initial Lumens</b>	2400
<b>Approx Mean Lumens</b>	1990
<b>Approx Initial Max Beam CP</b>	44000
<b>CT deg K</b>	3000
<b>CRI</b>	85+
<b>Beam Angle</b>	10°
<b>Rated Life</b>	10,000
<b>ANSI Ballast</b>	M130/O
<b>Fixt Rqmt</b>	Open
<b>Burning Position</b>	Universal
<b>Special Desc</b>	Magnetic Ballasts Not Recommended. See instruction's wiring diagram.
<b>Approvals</b>	IMERC

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335