

LED PL : DUAL MODE REPLACEMENT LAMPS

DESCRIPTION

LED PL Replacement Lamps directly replace fluorescent PL lamps at a fraction of the energy cost.

FEATURES

- Dual mode: operates on existing ballasts or line voltage
- Lasts 5x longer than compact fluorescent lamps
- Consumes up to 1/3 the energy of conventional CFL
- Base rotates for precision orientation once installed in fixture
- Shatter-resistant for reduced risk of injury and breakage
- Instant-on with no warmup, unlike CFLs
- Suitable for use in 6" cans
- Non-dimmable
- 12W items not for use in totally enclosed luminaires

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Commercial/Residential
- Hotel/Hospitality
- Education
- Healthcare
- Retail
- Property Management



5W
G23 Base



7W
GX23 Base



12W
GX23 Base



12W Horizontal
G24D Base



12W Horizontal
G24Q Base



12W Vertical
G24Q Base



PERFORMANCE	Power Consumption	5W	7W	12W
	Lumens	475/500	700	1,100
	Efficacy (LPW)	95/100	100	92
	CRI		80+	
	Beam		140°	
	CCT		2700K, 3000K, 3500K, 4000K	
	Life (L70)		50,000 hours	
ELECTRICAL	Power Factor		≥0.9	
	THD		<20%	
	Input Voltage		120-277V	
CONSTRUCTION	Base	G23, GX23, G24Q, G24D, GX24Q		
LISTINGS	Certification(s)	cULus Classified; LM70		
	Material Usage	RoHS Compliant; no mercury or lead		
	Environment	UL/cUL Classified for damp locations		

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	MOL	Orientation	Base	Life/Hours	Replaces Fluor
10172	LED5W2P/G23/827DM-G7B	475	5W	2700K	80+	4.13"	Vertical	G23	50,000	13W CFL
10173	LED5W2P/G23/830DM-G7B	475	5W	3000K	80+	4.13"	Vertical	G23	50,000	13W CFL
10174	LED5W2P/G23/835DM-G7B	475	5W	3500K	80+	4.13"	Vertical	G23	50,000	13W CFL
10180	LED5W2P/G23/840DM-G7B	475	5W	4000K	80+	4.13"	Vertical	G23	50,000	13W CFL
09782	LED5W2PH/G23/835DM-G7B	500	5W	3500K	80+	4.13"	Horizontal	G23	50,000	13W CFL
09626	LED7W2PH/G23/835DM-G7	700	7W	3500K	80+	5.82"	Horizontal	G23	50,000	18W CFL
10176	LED7W2P/GX23/827DM-G7B	700	7W	2700K	80+	4.78"	Vertical	GX23	50,000	18W CFL
10177	LED7W2P/GX23/830DM-G7B	700	7W	3000K	80+	4.78"	Vertical	GX23	50,000	18W CFL
09904	LED7W2P/GX23/835DM-G7B	700	7W	3500K	80+	4.78"	Vertical	GX23	50,000	18W CFL
10178	LED7W2P/GX23/840DM-G7B	700	7W	4000K	80+	4.78"	Vertical	GX23	50,000	18W CFL
09627	LED7W2PH/GX23/835DM-G7	700	7W	3500K	80+	6.1"	Horizontal	GX23	50,000	18W CFL
10163	LED12W2PH/GX23/827DM-G7*	1,100	12W	2700K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
10164	LED12W2PH/GX23/830DM-G7*	1,100	12W	3000K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
09629	LED12W2PH/GX23/835DM-G7*	1,100	12W	3500K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
10179	LED12W2PH/GX23/840DM-G7*	1,100	12W	4000K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
10166	LED12W4PH/G24Q/827DM-G7*	1,100	12W	2700K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
10167	LED12W4PH/G24Q/830DM-G7*	1,100	12W	3000K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
09630	LED12W4PH/G24Q/835DM-G7*	1,100	12W	3500K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
10168	LED12W4PH/G24Q/840DM-G7*	1,100	12W	4000K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
10169	LED12W4PV/G24Q/827DM-G7*	1,100	12W	2700K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
10170	LED12W4PV/G24Q/830DM-G7*	1,100	12W	3000K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
09631	LED12W4PV/G24Q/835DM-G7*	1,100	12W	3500K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
10171	LED12W4PV/G24Q/840DM-G7*	1,100	12W	4000K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
10473	LED12W2PH/G24D/835DM-G7	1,100	12W	3500K	80+	5.82"	Horizontal	G24D	50,000	26W CFL
10474	LED12W2PH/G24D/840DM-G7	1,100	12W	4000K	80+	5.82"	Horizontal	G24D	50,000	26W CFL

NOTE: Use order code when ordering. Visit eiko.com for complete ballast compatibility information. Not for use with emergency ballasts.
*Not for use in totally enclosed luminaires (12W only).

DIMENSIONS

