



# LED26WT8/48/850-G8D



<b>Description</b>	LED GLASS BYPASS/LINE VOLTAGE SINGLE ENDED DLCV4.3 T8 4FT 26W-3500LM 5000K 80+CRI Bi-Pin
<b>Ordering Code</b>	10468
<b>UNSPSC Code</b>	39101628

## Specifications

<b>Voltage Rating</b>	120/277
<b>Voltage Type</b>	AC
<b>Watts</b>	26
<b>Amps</b>	0.165
<b>mA</b>	240
<b>Lumens per Watt</b>	130
<b>Base Type</b>	G13
<b>Bulb Type</b>	T8
<b>MOL in/mm</b>	47.78/1213.6
<b>Length</b>	4'
<b>MOD in/mm</b>	1.10/28
<b>Lumens</b>	3380
<b>CT deg K</b>	5000
<b>CRI</b>	80
<b>Beam Angle</b>	160°
<b>Rated Life</b>	50000
<b>Ambient Operating Temp Range</b>	-20° C (-4° F) to 45° C (113° F)
<b>Approvals</b>	cULus

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335