



# MH-DE70/TD/UVS/3K



**Description**      **\*\*2BD\*\*** 70W 3000K UV Shield T6 RSC Double Ended Base

**Ordering Code**      15406

**UNSPSC Code**      39101614

Specifications	
<b>Watts</b>	70
<b>Base Type</b>	Recessed Single Contact (R7s)
<b>Bulb Type</b>	T6
<b>MOL in/mm</b>	4.50/114.3
<b>Mercury Content (mg)</b>	10.8
<b>HG Form</b>	liquid
<b>Approx Initial Lumens</b>	5200
<b>Approx Mean Lumens</b>	3400
<b>CT deg K</b>	3000
<b>CRI</b>	70
<b>Rated Life</b>	10,000
<b>Common Code</b>	HQI-DE 70/WDX
<b>ANSI Ballast</b>	M85/M98
<b>Fixt Rqmt</b>	Enclosed
<b>Burning Position</b>	Hor +/-45
<b>Special Desc</b>	Pulse Start & UV Shielded
<b>Coating</b>	Clear
<b>Approvals</b>	IMERC

watch > like > follow



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335