



EASY 3 COLORS
SELECCTOR
3500K • 4000K • 5000K



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
6000	6322	49 W
5000	5274	40 W
4000	4380	33 W

Based on 3500K, 85+ CRI. Actual wattage may vary +/- 5%

FEATURES

Shallow design is ideal for commercial, industrial and residential spaces requiring general illumination. Flexible design delivers continuous, uniform and glare-free illumination. Lightweight design enables easier installation. For use as general or task lighting in hallways, corridors, parking lots, educational, healthcare, office, and industrial applications.

LUMENS	4000/5000/6000
CCT	35K/40K/50K
CRI	85+
COLOR QUALITY	3 Step MacAdam Ellipse
LENGTH	4'
MOUNTING	Surface
DIMMING & CONTROL	0-10V Flicker Free 10% Dimming Standard (DIM10)
EMERGENCY	10W - Up to 1000L output
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



OPTICS & PERFORMANCE

The OIW-LED uses a prismatic acrylic lens to scatter the light emitted from the LED chips into functional light. The LED offered in the OIW-LED has the highest return on initial investment compared to other standard lighting solutions. Wrap around acrylic lens provides even illumination up to 180 degrees.

CONSTRUCTION

Heavy-duty 20-gauge cold rolled steel body. High-gloss white finish is pre-treated with 5-stage iron phosphate coating, which provides superior paint adhesion and protection against weathering. Painted high-gloss baked white enamel.

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers, rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00. Male and female 18-gauge 6 wire plug connectors are included with every luminaire to allow for simple, hassle-free continuous wiring. Each luminaire must be installed male to female.

OPTIONS

Fixtures can be shipped pre-installed with daylight harvesting controls, occupancy sensors, and/or power pack. Available manufacturer options include Leviton, Hubbell Automation, and others.

MULTI LUMEN/MULTI CCT

Easily field-selectable multi-lumen and multi-CCT selector switches allow you to easily change the intensity and CCT in the field.

DIMMING & DRIVER INFORMATION

DIM10 - Flicker Free 10% Dimming Standard (DIM10) 0-10V dimming on either MVOLT 120, 277V.

WARRANTY

Five-year warranty for parts and components. (Labor not included)

LISTINGS

c-UL-us - Listed for Feed Through Wiring.
Listed for DLC, California Title 24 compliant.

Example: **4-OIW-LED-4000L/5000L/6000L-DIM10-MVOLT-35K/40K/50K-85**

4	OIW	LED								
FIXTURE SIZE	SERIES	TYPE	LUMENS	DIMMING	VOLTAGE	CCT	CRI	EMERGENCY	WIRING IOPTION	
4 - 4'	OIW - LED General Linear	LED	4000L/5000L/6000L	DIM10 - 0-10V Dimming	MVOLT 347V	35K40K/50K	85	0-EMG-LED-10W	FBF - Internal Fast Blow Fuse SBF - Internal Slow Blow Fuse RIS - Radio Interference Filter	

OTHER OPTIONS
OSM3D-DDW-20 - HF Microwave Sensor 1-10 20% Dim
OSM3D-DDW-50 - HF Microwave Sensor 1-10 50% Dim
OSM3D-V1W - Line Voltage Microwave Sensor
USA - Made in America Compliance
FSP-311-B-D - 0-10V continuous dimming PIR photo/motion sensor with bluetooth control option.

