



#### APPLICATION:

Ideal for secure or high abuse areas, such as correctional facilities, institutions, schools, shopping centers, public buildings and airports.

#### PRODUCT FEATURES:

- Housing is die-formed heavy-gauge steel with white powder coat finish
- Neoprene gasket eliminates moisture, dust and insects
- Diffuser is injection-molded clear prismatic polycarbonate with UV inhibitors
- Drill points for maximum security
- Integral (molded) locking lugs opposite the retention screws
- Light source 1, 2 or 3 linear fluorescent tubes
- Standard stainless steel screws
- Wall or ceiling mounting for indoor or outdoor locations
- Lens attached to body with vandal resistance screws
- For continuous row mounting, please consult factor

- NEC required ballast disconnect is standard
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)

#### LISTING

UL/C-UL listed to US and Canadian standard

#### WARRANTY

Guaranteed for one year against mechanical defects

T8/T5  
OV1R

Fluorescent Vandal Resistant Linear

#### Ordering Information > Example: 4-OV1R-1-28-T5-EPS-MVOLT-EMG-T5-T5HO-700



FIXTURE SIZE	SERIES	WATTAGE	VOLTAGE	# OF BALLAST	BALLAST FACTOR
4 - 4'	OV1R-Oracle Vandal Resistant Linear Fluorescent Rectangle	<b>4' FIXTURE</b> 1-28-T5 (1 lamp/28W/T5) 1-54-T5HO (1 lamp/54W/T5HO) 2-28-T5 (2 lamps/28W/T5) 2-54-T5HO (2 lamps/54W/T5HO) 3-28-T5 (3 lamps/28W/T5) 3-54-T5HO (3 lamps/54W/T5HO) 1-32-T8 (1 lamp/32W/T8) 2-32-T8 (2 lamps/32W/T8) 3-32-T8 (3 lamps/32W/T8)	(Blank) - MVOLT (120/277) 120 277 347	(Blank) - 1 Ballast 2- 2 Ballasts	(Blank) - Normal BF

EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)	
ORDER CODE	DESCRIPTION
EMG-T8-BX-450	Up to 450 L. for T8 or BX
EMG-T8-BX-600	Up to 600 L. for T8 or BX
EMG-T8-BX-700	Up to 700 L. for T8 or BX
EMG-T8-BX-1400	Up to 1400 L. for T8 or BX
EMG-T5-T5HO-700	Up to 700 L. for T5 or T5HO
EMG-T5-T5HO-1300	Up to 1300 L. for T5 or T5HO
EMG-SD-T8-BX-T5-T5HO-1400	Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO
EMG-ICE-T8-BX-T5-T5HO-1400	ICE Pack 1400 L. for T8, BX, T5 or T5HO
GTD	Generator Transfer Device

#### BALLAST CONFIGURATION & CODE

17W/T8	32W/T8	14W/T5	24W/T5HO	28W/T5	54W/T5HO	DESCRIPTION
(Blank)	(Blank)	-	-	-	-	Electronic Instant Start
EPS	EPS	(Blank)	(Blank)	(Blank)	(Blank)	Electronic Program Start

Consult Factory for ADVANCE or LUTRON dimming ballast options.

#### WIRING OPTIONS

FBF	- Internal Fast Blow Fuse
SBF	- Internal Slow-Blow Fuse
RIS	- Radio Interference Suppressor

#### OTHER OPTIONS

INMS	- Motion Sensor
USA	- Made in America Compliance