

HH10PL

10" Architectural Horizontal CFL Downlight

Architectural


Catalog Number:

Project Name:

Type:

Note:

MAXILUME
ARCHITECTURAL LIGHTING



- A. Height = 8-7/8"
- B. Trim Aperture = 9-3/4"
- C. Cut-out = 10-1/2"
- D. Trim Outside Diameter = 11-1/8"
- E. Width = 17-3/4"
- F. Length = 16-3/4"

DESCRIPTION

1. LAMP HOLDER - Aluminum lamp holder effectively provides heat dissipation and ventilation. Unitized optics guarantees proper trim to housing installation. Tool-less installation adjustability from either outside the housing or inside the housing.

2. MOUNTING BRACKET - Constructed from 16-gauge steel and is supplied with C-channels that are adjustable up to 28". Mounting brackets may be adjusted up to 2-3/4" vertically from inside the housing.

3. RETAINING SPRINGS - Precision tooled springs secure trim to mounting frame, for effortless and tool-less installation.

4. JUNCTION BOX/BALLAST - UL listed for through-branch circuit wiring and has four 1/2" KO's, one 3/4" KO and four Romex knockouts with pry-out slots and strain clamps. Ballast and Junction Box are accessible from below, no tools required. Ballast supplied is manufactured by Philips Advance, Universal Technologies or Lutron Electronics.

5. MOUNTING FRAME - Die-formed construction for maximum heat dissipation and rust protection.

OPTICS

6. REFLECTOR - Self-flanged .050" aluminum reflector with low iridescent finish. Reflector provides 45-degree lamp-to-reflector image cutoff.

7. GROOVE BAFFLE - Self-flanged one-piece aluminum with concentric rings.

8. LENS - Choice of either tempered clear, tempered prismatic or tempered frosted lens fastened with two torsion springs for easy re-lamping. UL listed for wet or damp location.

LISTING

UL listed for through-branch circuit wiring and damp locations. Wet location only with lens trims.



LAMP BASE GUIDE (Sockets will accept all designated lamp bases listed.)						
13W	18W	26W	32W	42W	57W	70W
G24q-1 GX24q-1	G24q-2 GX24q-2	G24q-3 GX24q-3 GX24q-4	GX24q-3 GX24q-4	GX24q-4	GX24q-5	GX24q-6

HH10PL - ITEM SELECTOR: (Please check the boxes below for the option desired)

WATTAGE			BALLAST	VOLTAGE	EMERGENCY OPTIONS	TRIM TYPE & DESCRIPTION	REFLECTOR	BAFFLE
1 LAMP	2 LAMPS	3 LAMPS	<input type="checkbox"/> (E) Electronic <input type="checkbox"/> (M) Magnetic ¹ <input type="checkbox"/> (S) Energy Star ² <input type="checkbox"/> (DBL) Dual Ballast	<input type="checkbox"/> MVOLT (120/277) <input type="checkbox"/> 120 <input type="checkbox"/> 277 <input type="checkbox"/> 347	<input type="checkbox"/> EMG 750 (750 Lumens) ⁶ <input type="checkbox"/> EMG 1300 (1300 Lumens) ⁶ <input type="checkbox"/> INTG 750 (750 Lumens) ⁷ <input type="checkbox"/> INTG 1300 (1300 Lumens) ⁷ <input type="checkbox"/> EMG-D-750 (750 Lumens) ⁸ <input type="checkbox"/> INTG-D-750 (750 Lumens) ⁹ <input type="checkbox"/> ICE-1300 (1300 Lumens) ¹⁰	<input type="checkbox"/> 1501 <input type="checkbox"/> 1502 <input type="checkbox"/> 1503 <input type="checkbox"/> 1504 <input type="checkbox"/> 1505 <input type="checkbox"/> 1506 <input type="checkbox"/> 1514 <input type="checkbox"/> 1512 <input type="checkbox"/> 1515 <input type="checkbox"/> 1513	<input type="checkbox"/> CL <input type="checkbox"/> SCH ^{**} <input type="checkbox"/> SHZ ^{**} <input type="checkbox"/> WT <input type="checkbox"/> W <input type="checkbox"/> MB	<input type="checkbox"/> WH <input type="checkbox"/> P
<input type="checkbox"/> 1X9 <input type="checkbox"/> 1X13 <input type="checkbox"/> 1X18 <input type="checkbox"/> 1X26 <input type="checkbox"/> 1X32 <input type="checkbox"/> 1X42 <input type="checkbox"/> 1X57 <input type="checkbox"/> 1X70	<input type="checkbox"/> 2X9 <input type="checkbox"/> 2X13 <input type="checkbox"/> 2X18 <input type="checkbox"/> 2X26 <input type="checkbox"/> 2X32 <input type="checkbox"/> 2X42 <input type="checkbox"/> 2X57 <input type="checkbox"/> 2X70	<input type="checkbox"/> 3X9 <input type="checkbox"/> 3X13 <input type="checkbox"/> 3X18 <input type="checkbox"/> 3X26 <input type="checkbox"/> 3X32 <input type="checkbox"/> 3X42						

¹ - (M) Magnetic = Available on 9W, 13W, 18W & 26W fixtures only • ² - (S) Energy Star = Available on selected fixtures only, please see list above • ³ - MARK 7 = Must specify voltage • ⁴ - MARK 10 = Not available on 13W, 57W, 70W, must specify voltage • ⁵ - LUT-E (EC3D) = Not available on 13W, 57W, 70W, must specify voltage • ⁶ - EMG = Emergency battery pack w/ remote test switch • ⁷ - INTG = Emergency battery pack w/ integral (reflector) test switch • ⁸ - EMG-D = Emergency battery pack w/ remote test switch for damp location • ⁹ - INTG-D = Emergency battery pack w/ integral(reflector) test switch for damp location • ¹⁰ - ICE = Emergency battery pack w/ remote test switch operating between -18°C and 55°C • ¹¹ - FUSE = Single slow-blow fuse • ¹² - RIF = Radio interference filter

Specifications:

HH10PL _____
 WATT BALLAST VOLTAGE EMERGENCY OPTIONS TRIM TYPE REFLEC. BAFFLE RING

Sample of Catalog Number: HH10PL-1X32-E-MVOLT-EMG750-1501-CL-WH

REFLECTOR	BAFFLE	RING
CL Clear	WH White	WH Self-Flange White
SHZ Satin Haze (Low Iridescent)	P Black	Standard on all trims
WT Wheat		SCH** Self-Flange Chrome
MB Black		** Only available on XX01 CL
W White		SHZ* Satin Haze
		* Provided w/ satin haze ring only

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.



A division of
Elite Lighting

Submittal form is available @ www.maxilume.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions subject to change without notice.

10" Horizontal CFL Optics

Catalog Number:

Project Name:

Type:

Note:

MAXILUME
ARCHITECTURAL LIGHTING


1501-CL
Reflector



REFLECTOR FINISH: CL, WT, MB, SHZ, W
RING FINISH: WH, SCH, SHZ

A= 9-3/4" • B= 10-3/4"


1502-WH-CL
Baffle with Reflector



BAFFLE FINISH: WH, P
REFLECTOR FINISH: CL

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

1503-CL
Reflector with Fresnel Glass Lens




REFLECTOR FINISH: CL, WT, MB, SHZ, W
RING FINISH: WH

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1505-P
Baffle with Fresnel Glass Lens




BAFFLE FINISH: WH, P
REFLECTOR FINISH: CL

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1504-CL
Reflector with Prismatic Glass Lens




REFLECTOR FINISH: CL, WT, MB, SHZ, W
RING FINISH: WH

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1506-WH
Baffle with Prismatic Glass Lens




BAFFLE FINISH: WH, P
REFLECTOR FINISH: CL

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1514-CL
Reflector with Frosted Glass Lens




REFLECTOR FINISH: CL, WT, MB, SHZ, W
RING FINISH: WH

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1512-WH
Baffle with Frosted Glass Lens




BAFFLE FINISH: WH, P
REFLECTOR FINISH: CL

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1515-WT
Reflector with Tempered Clear Glass




REFLECTOR FINISH: CL, WT, MB, SHZ, W
RING FINISH: WH

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

1513-WH
Baffle with Tempered Clear Glass



BAFFLE FINISH: WH, P
REFLECTOR FINISH: CL

A= 9-3/4" • B= 10-3/4" • C= 1-3/4"

FOR
WET
LOCATION

MAXILUME
ARCHITECTURAL LIGHTING

A division of
Elite Lighting

Submittal form is available @ www.maxilume.com
Tel: 323-888-1973 • Fax: 323-888-1977

Specifications and Dimensions
subject to change without notice.

REV: MAXILUME-SPEC-03-23-2011