



Date _____

Project _____



**IP68
IP69K**
CERTIFIED



Static Color Options

Low-Profile Linkable LED Linear Luminaire for Color Effects in Harsh Environments

Product Features

Crisp True Colors

Available in RED, GREEN, BLUE, or AMBER

Secondary Optics

Available with a standard 120° beam or narrow focused 20° optics

Easy to Install Quick-Connect Cabling

Convenient push-and-click connectors and cabling make WPX Series fixtures easy to install and daisy chain

Embedded Aluminum Heatsink

Embedded aluminum heatsink provides ample cooling for a long lifetime and allows the fixture to operate in cold and hot weather environments

Superior Chemical & UV Resistance

Seamless polymeric outer shell provides IP68/IP69K ingress protection and is specialized for superior chemical resistance. An additional protective coating is available which integrates a UV inhibitor and UV blocker for outdoor applications.

Warranty

3 Years (See ggled.net for Terms)

Mounting

Ceiling or Wall

Dimensions

Length Varies, Width 1.25" x Height 1.75"


Ordering Information

Product	Length	Color	Optics	Dimming	UV Protection	Through Wired
WPX						
4 4-Foot	RED RED (623 nm)	BLU BLUE (470 nm)	Blank (standard) No Secondary Optics 120° Beam Angle	Blank (standard) No Dimming	Blank (standard) No Coating, Rated for Indoor Use	Blank (standard) Connectors on Input & Output for ability to Daisy Chain fixtures
6 6-Foot	GRN GREEN (528 nm)	AMB AMBER (590 nm)	020 Added Spot Optics 20° Beam Angle	DIM 0-10V Dimming	UVO Outdoor-Rated With UV-Blocking Coating	SE (Single-Ended) Connector on Input Only, No Daisy Chain, for Standalone Install
8 8-Foot						

Power & Connection Accessories

Cable	Type	Length	Wire	Power Supply	Max Output	Enclosure	Voltage
WPX-JMP-1	Jumper	1ft / End-to-End	14 AWG SJOOW	WPX-PSU-80	80W	IP67	120-277 VAC
WPX-JMP-2	Jumper	2ft	14 AWG SJOOW	WPX-PSU-120	120W	IP67	120-277 VAC
WPX-JMP-4	Jumper	4ft	14 AWG SJOOW	WPX-PSU-240	240W	IP67	120-277 VAC
WPX-JMP-8	Jumper	8ft	14 AWG SJOOW	WPX-PSU-320	320W	IP67	120-277 VAC
WPX-JMP-12	Jumper	12ft	14 AWG SJOOW	WPX-PSU-480	480W	IP67	120-277 VAC
WPX-JMP-16	Jumper	16ft	14 AWG SJOOW	WPX-PSU-600	600W	IP67	120-277 VAC
WPX-JMP-20	Jumper	20ft	14 AWG SJOOW				
WPX-LDR-8	Leader Cable	8ft	14 AWG SJOOW				
WPX-LDR-25	Leader Cable	25ft	14 AWG SJOOW				

Mounting Hardware	Description
WPX-MNT-NM	Non-Metallic Quick Latch
WPX-MNT-SS	Stainless Steel Bolt Latch



Low-Profile Linkable LED Linear Luminaire for Color Effects in Harsh Environments

Product Specifications

Construction & Materials

Convenient push-and-click connectors let you easily and rapidly install Leader Cables and Jumper Cables. Multiple cable lengths support a variety of layouts.

Integrated aluminum heat spreader.

Seamless copolyester outer shell provides IP68/IP69K ingress protection and is specialized for superior chemical resistance. Additional protective coating is available which integrates a UV inhibitor and UV blocker for outdoor applications.

All G&G luminaires and components (with the exception of our LED boards and drivers) are proudly manufactured and assembled in the USA.

Electrical System

Power Factor: 0.9 nominal.

Input Power: Stays consistent over life.

Temperature Rating: Designed to operate in temperatures -40°C to 55°C.

Total Harmonic Distortion: < 20%

Regulatory Qualifications

cULus listed.

IP68/IP69K system.

UL listed for wet locations.

Data: Power Requirements

Length & Output	Fixture Watts	Fixtures Supported per Power Supply					
		PSU-80	PSU-120	PSU-240	PSU-320	PSU-480	PSU-600
WPX8 - COLOR	100 W	0	1	2	2	4	5
WPX6 - COLOR	100 W	0	1	2	2	4	5
WPX4 - COLOR	50 W	1	2	4	4	7	9