

Twist-Lock® Devices 30A, 125V AC, 2 Pole, 3 Wire Grounding Corrosion Resistant Valise® Plug

HUBBELL

Features

- Powerful cord grip prevents conductor slippage and strain on wiring terminals
- Totally insulated impact and crush resistant nylon body
- Unique patented corrosion resistant clamp type terminals provide a superior electrical connection by bundling the conductor strands when clamps are tightened



Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	783585808215	HBL26CM11V

Listings

Listed to UL 498
Fed.Spec. W-C-596
Certified to CSA C22.2 No.42

Accessories

Connector	HBL26CM13V
Single Receptacle	HBL26CM10
Weatherproof Boot	HBL60CM31V

Specifications

Blades	Brass - Nickel plated
Terminal Clamps	Silicon Bronze - Nickel plated
Terminal Screws	#8 - 32 Stainless Steel (Philips / Slotted / Robertson)
Housing	Yellow nylon
Clamp Screws	#8 - 32 Stainless Steel - (Philips / Slotted / Robertson)

Resources

[eCatalog](#)

Performance

Electrical

Current Interrupting	Certified for full rated current
Dielectric Voltage	Withstands 2,000V minimum

Mechanical

Terminal Accommodation	#18 AWG - #10 AWG stranded copper wire only.
------------------------	--

Terminal Identification	Terminals identified in accordance with UL 498
-------------------------	--

Environmental

Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Moisture Resistance	IP20 Suitability
Operating Temperatures	Maximum Continuous 75°C Minimum -40°C (w/o impact)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

