



Product Number: 20644

Order Abbreviation: CF26DD/E/835/ECO/BL/1

General Description: DULUX 26W double compact fluorescent lamp with 4-pin base, 3500K color temperature, for use with electronic and dimming ballasts, packaged one per blister

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	CF26DDE835ECOBL1 6/CS 1/SKU
Average Rated Life (hr)	10000
Base	G24Q-3
Bulb	T12
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	3500
Diameter (in)	0.000
Diameter (mm)	0.00
Family Brand Name	Dulux® D/E
Initial Lumens at 25C	1800
Mean Lumens at 25C	989
Maximum Overall Length - MOL (in)	6.5
Maximum Overall Length - MOL (mm)	2.5
Nominal Wattage (W)	26.00

Footnotes

- Approximate initial lumens after 100 hours operation.
- 2 pin CF lamps are not suitable for use in frequently cycled applications or with occupancy sensors. 2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Caution: DULUX EL Circline units cannot be used on dimming circuits, emergency exit fixtures or lights, electronic timers, photocells or lighted switches. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits.
- Lumen output and life rated on high frequency operation.
- DULUX F lamps can typically be operated on DULUX L and PENTRON HO ballasts of the same/similar wattage. Check with the ballast manufacturer to verify lamp/ballast compatibility.
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.