



**Product Number:** 20454

**Order Abbreviation:** CF26DT/827/ECO

**General Description:** DULUX 26W triple compact fluorescent lamp with 2-pin base, 2700K color temperature, 82 CRI for use on magnetic ballast

#### Product Information

|                              |                          |
|------------------------------|--------------------------|
| Abbrev. With Packaging Info. | CF26DT827ECO 50/CS 1/SKU |
| Average Rated Life (hr)      | 12000                    |
| Base                         | GX24D-3                  |
| Bulb                         | T4                       |
| Color Rendering Index (CRI)  | 82                       |
| Color Temperature/CCT (K)    | 2700                     |
| Initial Lumens at 25C        | 1800                     |
| Nominal Voltage (V)          | 105.00                   |
| Nominal Wattage (W)          | 26.00                    |



#### Footnotes

- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- 2 pin CF lamps are not suitable for use in frequently cycled applications or with occupancy sensors. 2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit.
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit [www.lamprecycle.org](http://www.lamprecycle.org)
- Mean lumens are measured at 40% of average rated lamp life.
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).