


LED PAR56 LAMPS

SPOT, NARROW FLOOD & FLOOD LAMP



VOLTAGE



OPERATING TEMP



CRI



RATED LIFE



WARRANTY

directional efficiency



LED-7356-SP
LED-7356-NF



LED-7356-FL

- Available in three different beam angles: Spot, Narrow Flood and Flood
- Forward-phase, Line Voltage Dimmable
- Suitable for Damp Locations
- Available in 3000, 4000 and 5000K
- High lumen output
- Base Type: GX16d
- Rated for use in totally enclosed luminaires

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT	DIMENSIONS	BEAM ANGLE
LED-7356-SP30	844006055899	300W Halogen	40W	3500	3000K	7 x 7 x 5 in.	15°
LED-7356-SP40	844006055905	300W Halogen	40W	3500	4000K	7 x 7 x 5 in.	15°
LED-7356-SP50	844006055912	300W Halogen	40W	3500	5000K	7 x 7 x 5 in.	15°
LED-7356-NF30	844006055929	300W Halogen	40W	3500	3000K	7 x 7 x 5 in.	25°
LED-7356-NF40	844006055936	300W Halogen	40W	3500	4000K	7 x 7 x 5 in.	25°
LED-7356-NF50	844006055943	300W Halogen	40W	3500	5000K	7 x 7 x 5 in.	25°
LED-7356-FL30	844006055950	300W Halogen	40W	3500	3000K	7 x 7 x 5 in.	40°
LED-7356-FL40	844006055967	300W Halogen	40W	3500	4000K	7 x 7 x 5 in.	40°
LED-7356-FL50	844006055974	300W Halogen	40W	3500	5000K	7 x 7 x 5 in.	40°



LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
 847.380.3540 • led-llc.com

