

HYBRID 365

FREE TO SHINE

NEW! Solera Solar Lighting Hybrid 365 introduces game-changing technology to leverage both solar and line voltage to power bright LED area lights, all night - every night. Hybrid 365 has an intelligent control module that knows to switch from cost-free solar power to line voltage only when the battery is depleted. Solera Solar Lighting's unique all-in-one design delivers high performance, ease of installation and adjustability - unlike any other solar lighting.



- Hybrid 365 area light switches from cost-free solar to line voltage, only when the long-lasting battery is depleted
- All-in-one design
- Exclusive long-lasting battery withstands extreme temperatures
- Easy to install and operate
- Adjustable solar panel multiple mounting and lens types available
- Infrared Remote Control to adjust brightness
- Slip-fitter bracket included with fixture
- Power Dimming: Continuous from 20% to 100% output power, more that 100 steps adjustment
- Fixture Operating Temperature Range = -40°F to 140°F Battery Charging Temperature Range = -4°F to 140°F

PART #	UPC	COMPARABLE TO	WATTAGE**	LUMENS	сст	EPA
SL-SAL-HYB-30W-40K-SF-YY-G1	844006051051	250W	30W	5900	4000K	4.45

YY = Body color, BK : black...etc

FC (II)



















solera-solar.com

847.380.3540





Grid power uses 45W




FREE TO SHINE


HYBRID 365

LED SOLAR AREA LIGHT COMPARES TO 250W HID


Fixture Side View



Fixture Top View



(Total fixture weight = 30lbs)



ADDITIONAL BRACKETS MUST BE PURCHASED SEPARATELY (SLIP-FITTER BRACKET INCLUDED WITH FIXTURE)

REMPHOS PART # DESCRIPTION

SL-SAL-HYB-BKT-30W-RP-G1 Square pole bracket

SL-SAL-HYB-BKT-30W-TN-3-G1 3" square tenon bracket

SL-SAL-HYB-BKT-30W-RT-3-G1 3" round tenon bracket

SL-SAL-HYB-BKT-30W-WM-G1 Wall mount bracket











SL-SAL-HYB-BKT-30W-SP-G1

SL-SAL-HYB-BKT-30W-TN-3-G1

SL-SAL-HYB-BKT-30W-RT-3-G1 SL-SAL-HYB-BKT-30W-WM-G1

Default Setting - No Adjustments Necessary

The default setting is Dusk 'till Dawn @ 80% first 2 hours, 50% constant & 80% w/ motion for the rest of the night.





HYBRID 365

LED SOLAR AREA LIGHT

FREE TO SHINE

Save with Solera Solar Lighting™ Hybrid 365

Innovative Solera Solar Lighting Hybrid 365 area lights reduce your reliance on the high cost power grid. Our exclusive intelligent control model minimizes use of line voltage to only when the long-lasting solar battery is depleted. Hybrid 365 is an economic and sustainable solution that substitutes free solar energy for line voltage during peak demand times such as summer days. See examples below of potential annual savings with Solera Solar Lighting Hybrid 365 area lights.

Estimated Annual Energy Savings With Solera Solar Lighting™ Hybrid 365 Area Lights*

	Annual Cost to Operate	Annual Cost to	ESTIMATED	ED ANNUAL ENERGY SAVINGS			
	HYBRID 365 30W Line Voltage	Operate HID 250W Line Voltage	1 Area Light	x25 Area Lights	x100 Area Lights		
Boston, MA	\$6.32	\$203.09	\$196.77	\$4,919.25	\$19,677.00		
New York, NY	\$4.60	\$163.75	\$159.15	\$3,978.75	\$15,915.00		
Montreal, Quebec CAN	\$6.49	\$188.35	\$181.86	\$4,546.50	\$18,186.00		
Nashville, TN	\$2.79	\$107.45	\$104.67	\$2,616.75	\$10,467.00		
Miami, FL	\$1.63	\$119.18	\$117.55	\$2,938.75	\$11,755.00		
Chicago, IL	\$4.17	\$105.43	\$101.26	\$2,531.50	\$10,126.00		
Portland, OR	\$2.73	\$95.80	\$93.07	\$2,326.75	\$9,307.00		
Santa Maria, CA	\$1.73	\$186.60	\$184.88	\$4,622.00	\$18,488.00		

^{*}Assumes default setting of Dusk 'till Dawn @ 80% first 2 hours, 50% constant & 80% w/ motion detected for the rest of the night. Area lights are fully programmable to adjust setting. Sources for Calculations: Peak Sun Hours or Solar Radiation information https://www.nrel.gov/gis/solar.html, Sunrise and Sunset Times https://www.timeanddate.com/astronomy/usa, Line Voltage Costs (cents/kWh) https://www.eia.gov/electricity/state/

Solera Solar Lighting™ Hybrid 365 Solar Energy Use** by Season

	Summer	Winter	Spring/Fall	Annual		
Boston, MA	71%	35%	64%	57%		
New York, NY	82%	36%	68%	62%		
Montreal, Quebec CAN	72%	26%	61%	53%		
Nashville, TN	83%	38%	71%	64%		
Miami, FL	94%	63%	85%	81%		
Chicago, IL	68%	17%	53%	46%		
Portland, OR	98%	22%	70%	63%		
Santa Maria, CA	100%	66%	82%	83%		

^{**}Average annual percentage of time in use based on: Peak Sun Hours or Solar Radiation information https://www.nrel.gov/gis/solar.html, Sunrise and Sunset Times https://www.timeanddate.com/astronomy/usa. Balance of percentage of time is powered by line voltage.





HYBRID 365

FREE TO SHINE

PART NUMBER BUILDER

MFR	PRODUCT	TYPE	WATTAGE	COLOR	FUNCTION	BODY COLOR	VOLTAGE	GEN	LENSE
SL	SAL	HYB	30W	XX	SF	YY		G1	
				-30K=3000K		-BK=Black	-(HV)		T2=TYPE 2 LENS

-30K=3000K -40K=4000K

-50K=5000K

ORDERING GUIDE	
30W HYBRID 120-277V	30W HYBRID HIGH VOLTAGE 480V (HV)
SL-SAL-HYB-30W-40K-SF-BK-G1	
SL-SAL-HYB-30W-30K-SF-BK-G1	
SL-SAL-HYB-30W-50K-SF-BK-G1	
SL-SAL-HYB-30W-30K-SF-BK-G1-T2	SL-SAL-HYB-30W-30K-SF-BK-HV-G1-T2
SL-SAL-HYB-30W-30K-SF-BK-G1-T3	SL-SAL-HYB-30W-30K-SF-BK-HV-G1-T3
SL-SAL-HYB-30W-30K-SF-BK-G1-T4	SL-SAL-HYB-30W-30K-SF-BK-HV-G1-T4
SL-SAL-HYB-30W-30K-SF-BK-G1-T5	SL-SAL-HYB-30W-30K-SF-BK-HV-G1-T5
SL-SAL-HYB-30W-40K-SF-BK-G1-T2	SL-SAL-HYB-30W-40K-SF-BK-HV-G1-T2
SL-SAL-HYB-30W-40K-SF-BK-G1-T3	SL-SAL-HYB-30W-40K-SF-BK-HV-G1-T3
SL-SAL-HYB-30W-40K-SF-BK-G1-T4	SL-SAL-HYB-30W-40K-SF-BK-HV-G1-T4
SL-SAL-HYB-30W-40K-SF-BK-G1-T5	SL-SAL-HYB-30W-40K-SF-BK-HV-G1-T5
SL-SAL-HYB-30W-50K-SF-BK-G1-T2	SL-SAL-HYB-30W-50K-SF-BK-HV-G1-T2
SL-SAL-HYB-30W-50K-SF-BK-G1-T3	SL-SAL-HYB-30W-50K-SF-BK-HV-G1-T3
SL-SAL-HYB-30W-50K-SF-BK-G1-T4	SL-SAL-HYB-30W-50K-SF-BK-HV-G1-T4
SL-SAL-HYB-30W-50K-SF-BK-G1-T5	SL-SAL-HYB-30W-50K-SF-BK-HV-G1-T5
	30W HYBRID 120-277V SL-SAL-HYB-30W-40K-SF-BK-G1 SL-SAL-HYB-30W-30K-SF-BK-G1 SL-SAL-HYB-30W-50K-SF-BK-G1-T2 SL-SAL-HYB-30W-30K-SF-BK-G1-T3 SL-SAL-HYB-30W-30K-SF-BK-G1-T4 SL-SAL-HYB-30W-30K-SF-BK-G1-T5 SL-SAL-HYB-30W-40K-SF-BK-G1-T2 SL-SAL-HYB-30W-40K-SF-BK-G1-T3 SL-SAL-HYB-30W-40K-SF-BK-G1-T3 SL-SAL-HYB-30W-40K-SF-BK-G1-T4 SL-SAL-HYB-30W-40K-SF-BK-G1-T5 SL-SAL-HYB-30W-50K-SF-BK-G1-T2 SL-SAL-HYB-30W-50K-SF-BK-G1-T2 SL-SAL-HYB-30W-50K-SF-BK-G1-T3 SL-SAL-HYB-30W-50K-SF-BK-G1-T3 SL-SAL-HYB-30W-50K-SF-BK-G1-T3

^{*}Custom orders will be fulfilled at our Innovation and Manufacturing Center in Middleton, MA. (Lead time is 1-2 weeks)

