



Type IC, Air-Tight, Wet & Plenum

DESCRIPTION

4" Round Recessed LED With Integral Driver In Connection Box Commercial Grade Quality With Architectural Design


FEATURES & BENEFITS

2" Deep - Install Where Ceiling Space Is Limited
Type IC Rated - No Housing Required
CRI 90+ for True Color Rendering
Fast & Easy To Install - Save On Labor
Driver Inside Connection Box - No Junction Box Needed
Armored Cable & Metal Connectors - Open Plenum Rated

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 2"

DIMENSIONS: ID 4" OD 5" Cut Out 4" to 4 1/4"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as Cat # LLL-LD1535TR

ORDERING GUIDE Example: LL4RR - 30K - WH

	CCT	Trim Finish	
LL4RR	-	-	
2700K	27K	WH	White
3000K	30K	BK	Black
4000K	40K		

LL4RR

4" Round Regressed 2nd Gen Plenum LED 14.5W

Notes:	
Cat #:	Qty:
Location:	
Project:	

SPECIFICATION					
Applications	Recessed Ceiling Mount				
Energy Used	14.5 W				
Color Temperature	2700	3000	4000		
Light Output	950	1000	1020		
Halogen Equivalent	90 W				
Beam Angle	90°				
CRI	90 +				
Default Driver Input	120V AC		riac Dimmable		
Optional Driver Input	120V-347V AC 0-1		-10V Dimmable		
Power Factor	0.95				
Approved Location	Insulated Ceilings, Open Plenum, Wet				
IP Rating	IP 54				
Air Tight	Yes				
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)				
Projected Life	70% Light Output at 50,000 Hours				
Certification	cULus, Energy Star, T24				
Warranty	10 Year on Residential				
vvairailty	5 Year on Commercial Applications				

AVAILABLE TRIMS





White

Black

ACCESSORIES

Sold Separately



Armored Low Voltage Extensions 10ft - cat #**MEC10** FT6 / CMP rated. Max 40 ft Allowed



Flat Rough-In Plates - cat #RIP4



Flanged Rough-In Plate - cat #FRP4



Goof Ring OD 5 3/4"
White cat # GR4 Black cat # GR4-BK

COMPLIANCE









Type IC Air-Tight Open Plenum