

LRG3-HO-IT

3" Round Regressed Gimbal LED High Output 11W - Trimless

Project: _____

Location: _____

Model #: _____ Qty: _____

Notes: _____

DESCRIPTION


3" Round Regressed Trimless Gimbal LED
 With Integral Driver In Connection Box
 Gimbal Yet Air-Tight Without Housing Needed

FEATURES & BENEFITS

3 1/2" Deep - Install Where Ceiling Space Is Limited
 Invisible Trim for High-End Contemporary Installations
 Type IC Rated - No Housing Required
 Air-Tight & Wet Location rated
5CCT user selectable 2700-3000-3500-4000-5000K
 or **Dim to Warm** 3000K to 1800K options
 CRI 90+ for True Color Rendering
 Driver Inside Connection Box - No Junction Box Needed
 Twist & lock mounting of fixture to trim

DIMENSIONS: ID 3 1/8" OD 4 3/4" Cut Out 3 1/8"

Ceiling Clearance Required: 4"



120V TRIAC Dimmable Optional 120V-347V

Driver Included



Driver 0-10V Dimmable
 Order Separately as
model # LLL-LD1025T3

ORDERING GUIDE

LRG3-5CCT-HO-IT-WH

[5CCT White Trim](#)



LRG3-5CCT-HO-IT-BK

[5CCT Black Trim](#)

LRG3-3018K-HO-IT-WH

[Dim to Warm White Trim](#)

LRG3-3018K-HO-IT-BK

[Dim to Warm Black Trim](#)

SPECIFICATION	
Applications	Sloped Ceilings up to 20°, General Lighting Trimless
Power	11 W
Color Temperature	5CCT: 2700 3000 3500 4000 5000 DTW 30-18K
Light Output	920 950 1020 1050 1050 770
Halogen Equivalent	90 W
Beam Angle	38° Beam with 20° tilt and 360° rotation
CRI	90 +
Default Driver Input	120V AC Triac Dimmable
Optional Driver Input	120V-347V AC 0-10V Dimmable
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG
Power Factor	0.95
Approved Location	Insulated Ceiling & Wet Locations
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cULus
Warranty	10 Year Residential / 5 Year Commercial

AVAILABLE TRIMS



White



Black

ACCESSORIES

Sold Separately




Low Voltage Extension Cables. Max 40 ft Allowed
[6ft - model # EXC6](#)
[20ft - model # EXC20](#)

Mounting Plate

We do not have suitable mounting plate currently

COMPLIANCE



**Type IC & Air-Tight
 Wet Location**

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
 Hainesport NJ, Naples FL, Vancouver WA

www.LotusLEDLights.com

mailing addresses
 warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
 Delta BC & Mississauga ON