COUNTERMAX MX-LD-AC I UNDERCABINET LED DISC

53830 / 53832 / 53835 / 53836


- Surfaced or Recessed installation with 30°swivel
- Available in 2700K and 3000K Color Temperature, CRI 90+
- Line Voltage Construction, no driver needed
- Aluminum heat sink
- Link up to 20 units on single power supply
- Dimmable with Triac Dimmer
- Not suitable for enclosed cabinets
- Comes individual or in packs (3 pucks)





PRODUCT DESCRIPTION

The versatile MX-LD-AC LED disc features two piece aluminum construction that allowing for surface mounting all recessed. They are designed for daisy chain installation of up to 20 discs on one power supply. Fully dimmable with ELV and Triac dimmers. This combination of versatility, safety, energy efficiency and dimmability make the MX-LD-AC LED discs the smart choice for disc lighting.



MEASUREMENTS

MEASUKEMENIS								
MODEL	DISC	DIMENSION	HANGING WEIGHT					
53830	1	2.75"D x 1"H	0.38 lb					
53832	1	2.75"D x 1"H	0.38 lb					
*53835	3	2.75"D x 1"H	1.50 lb					
*53836	3	2.75"D x 1"H	1.50 lb					

LAMPING

	LUML		LING	13 COL					
MODEL	BULB TYPE	CRI	INIT.	DEL	TEMP.	DIMMABLE	INPUT		
53830	1 x 4W PCB LED (Integrated)	90+	250	200	3000K	Triac CL	120V		
53832	1 x 4W PCB LED (Integrated)	90+	250	200	2700K	Triac CL	120V		
*53835	3 x 4W PCB LED (Integrated)	90+	250	200	3000K	Triac CL	120V		
*53836	3 x 4W PCB LED (Integrated)	90+	250	200	2700K	Triac CL	120V		
*Kit required (sold separately)									

HIMENS

COL

INCLUDES:

- Two mounting screws
- One 12" Connecting Cord



Two piece Aluminum Construction for both Surface and Recessed Installation











Always consult a qualified electrician before installing any lighting product





WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

FINISHES:

BRONZE (BZ)

SATIN NICKEL (SN)

WHITE (WT)



Aluminum

RATINGS

ETL/cETL Dry Location Dimmable Title 24 JA8 Complaint **Energy Star**









ADDITIONAL:

ROTATION : 30° SWIVEL RATED LIFE : 35,000 Hours

OPERATING TEMP PHOTOMETRIC

: -20° C (-4°), 40°C (104°F) : Report Found Online