

NOTES.


PROJECT NAME: _____CATALOG NUMBER:__

FIXTURE SCHEDULE:

Page: 1 of 2

LED HIGH BAY DIRECTFIT **MHD** Series

PRODUCT DIMENSIONS:



PRODUCT DESCRIPTION:

The LED High Bay DirectFit Lamp is the plug-and-play replacement for high output metal halide bulbs in non-enclosed high bay fixtures. The lamp screws directly into Mogul-based sockets and operates off existing CWA ballasts - no rewiring or extra labor required! The DirectFit lamp delivers high quality light using 66%-75% less energy than the 750W and 1000W metal halide bulbs it replaces.

FEATURES:

- 250W- replaces 1,000W MH
- Vertical Mogul sockets
- · Powered by existing ballast, input voltage to ballast 120-480V
- E39, EX39, E40 lamp base
- 5 year standard warranty
- 60,000 hours L70 rated lamp life
- 5000K CCT
- Not for use in totally enclosed luminaires

CONSTRUCTION:

• 3.7 lbs

APPLICATION:

- Sawmills
- Refineries
- Aerospace
- Convention Centers
- Sports Arena

WARRANTY:

5-year standard warranty (further details available at www.maxlite.com/warranties) Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

MODEL SELECTION (Full list of order codes on pg. 2)	Typical order example: 250MH750	
250	МН	750
WATTAGE	FAMILY	CRI & CCT
250= WATTAGE	MH= METAL HALIDE RETROFIT	750= CRI70, 5000K





LED HIGH BAY DIRECTFIT MHD Series

Page: 2 of 2

SPECIFICATIONS:

		250MH750	
	Lumens Delivered (Im)	37,000	
	Efficacy (Im/W)	148	
GENERAL	Color Temperature	5000K	
PERFORMANCE	Input Power (W)	250	
	CRI	≥70	
	Lumen Maintenance (L70, TM-21 @ 25°C)	60,000	
ELECTRICAL	Input Voltage	Powered by existing ballast, input voltage to ballast 120-480V	
	Material Usage	RoHS compliant; no mercury	
	Environment	Indoor, Dry Location	
CERTIFICATION	Certification	cULus Listed	
CERTIFICATION	Warranty	5year standard warranty	
	Operating Temperature	-4°F - 131°F	
	Humidity	15%-85% RH, non condensing	

ORDERING*:

ORDER CODE	MODEL	VOLTAGE	WATTAGE	ССТ
14101700	250MH750	Powered by existing ballast, input voltage to ballast 120-480V	250	5000K

	1000W
PRODUCT	250MH750
TOTAL LUMENS	37,000
LAMP WATTS	250W
LM/WT	148 lm/W

