

	Pro	duct Spec	
Category	LED Slim Canopy		and the little is a second of the later.
Item Code	9414		
Stock Code	FX10SCM28/840/BK	PICTURE	
Mounting	Ceiling		
Housing Color	Black		

Electric Characteristics		Photometric Cha	Photometric Characteristics		
Rated Wattage (W)	28	Lumen (lm)	3512		
Tested Wattage (W)	28.19	Efficacy (lm/w)	125		
Input Voltage (V)	100~277	CRI	80		
Voltage Frequency (Hz)	50/60	сст (к)	4000		
nput Current (A)	0.31	Beam Angle (∘)	160		
Power Factor	>0.9	General Characteristics			
Replacement Wattage (W)	150	Operating Temperature	-22°F~122°F		
Surge protect level	4KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10	IP rating	IP65		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
Product Dimensions		Suggested Accessory			
Weight (lbs.)	4.5	Microwave	Microwave Sensor		
Height (in)	3.5	EM dri	EM driver		
Length (in)	9.48				
Width (in)	9.48				
Mounting Height (ft)					
Cable Length (ft)					
	Qual	ifications			
UL/ETL	ETL/cETL	LM79	٧		
Energy Star		LM80	٧		
DLC	5.0 Premium	IES File	٧		
CEC		FDA			
JA8		NEMA			
FCC	٧	Dimmer List			
RoHS	٧				

Version 1.2, 4/6/2020