NOTURALED[®] Product Engineering Spec

	Produ	uct Spec			
Category	LED Slim Canopy				
Item Code	9415		ll l	A DECEMBER OF THE OWNER OWNER OF THE OWNER OWNER OWNER OWNER OWNER OWNE OWNER OWNE OWNE OWNE OWNE OWNE OWNE OWNE OWNE	
Stock Code	FX10SCM28/850/BK	PICTURE			
Mounting	Ceiling				
Housing Color	Black				
	c Characteristics			ric Characteristics	
Rated Wattage (W)	28		Lumen (lm)	3512	
Tested Wattage (W)	28.19	Efficacy (lm/w)		125	
Input Voltage (V)	100~277		CRI	80	
Voltage Frequency (Hz)	50/60		ССТ (К)	5000	
Input Current (A)	0.31		Beam Angle (°)	160	
Power Factor	>0.9		General Characteristics		
Replacement Wattage (W)	150	Operating Temperature		-22°F~122°F	
Surge protect level	4KV	Storage Temperature		-40°F~140°F	
Dimmable	1-10	IP rating		IP65	
THD	<20%		Rated Life	50000 hrs	
			Warranty	5 years	
			-		
Prod	uct Dimensions		Suggested Accessory		
Weight (lbs.)	4.5		Micro	wave Sensor	
Height (in)	3.5		Е	M driver	
Length (in)	9.48				
Width (in)	9.48				
Mounting Height (ft)					
Cable Length (ft)					
	Oualif	fications			
UL/ETL	ETL/CETL		LM79	V	
Energy Star	, •		LM75	.√	
DLC	5.0 Premium		IES File	v V	
CEC	Sio Freinfum		FDA	v	
JA8			NEMA		
FCC	V		Dimmer List		
RoHS	v v		Diminer List		
ROHS Comments:	v				