

PROJECT:	
SCHEDULE:	DATE:
PREPARE BY:	
NOTES:	

FDL 6X6 FLOODLIGHT (Selectable Wattage)

DESCRIPTION

naturaLED® 6X6 selectable wattage floodlights provide a range of sizes and wattages to fit your needs. Our floodlights has a flood beam distributions and replaces up to 575 watt. This product is water resistant rated at IP65. Creating bright, security and spot lighting for a variety of applications such as perimeter, entryway, facades, landscapes, retail and residential complexes and architectural lighting. Pre-installed yoke-arm or knuckle-mount design can be adjustable to the angle that best suit your needs.

APPLICATIONS

Security, Architectural, Perimeter, Entryway, Pathway, Landscape



**Rated Life 50,000 Hours
Warranty 5 Years**

FEATURES

- DLC Premium
- IP65 Rated
- UL Listed
- ColorTemp: 4000K, 5000K
- 1/2" NPT stainless steel threaded nipple
- Selectable Wattages (3 Wattages)
- Input line voltage: 120-277V
- CRI: 70
- Powerfactor >0.9
- Surge Protect Level: 6KV
- Dimmable: 1-10V
- Beam Angle: NEMA 6X6
- Material: Aluminum Die-Cast
- Operating temperature: -40°F - 113°F
- 5 Year Warranty
- Finish: Bronze (RAL#8019)
- 4-feet SO Cord for easy installation
- Recommended Mounting Height: 10-26 feet

ACCESSORIES

- Photocell Kit
- Slip Fitter Mount
- Surge Protector 120-277V

SAMPLE NUMBER FFXFDL150SW/66/40K/BZ-YK

FAMILY	SERIES	WATTAGE	BEAM ANGLE	COLOR TEMP	COLOR	COLOR
FX fixture	FDL floodlight	150SW 100/130/150 wattage selectable	66 6X6 NEMA	40K 4000K	BZ Bronze	YK YK- Yoke Mount KNC- Knuckle Mount



6X6 FLOODLIGHT SW

FLOODLIGHTS & AREA LUMINAIRES

*P= Premium DLC / *S = Standard DLC

ORDERING

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Mount	IP65 Rated	DLC (S/P)
100	9567	FXFDL150SW/66/40K/BZ-YK	4000K	13,500	400	Yoke	●	P
130				16,900				
150				20,890				
100	9568	FXFDL150SW/66/50K/BZ-YK	5000K	13,000	400	Yoke	●	P
130				16,900				
150				21,028				
100	9569	FXFDL150SW/66/40K/BZ-KNC	4000K	13,500	400	1/2" Knuckle	●	P
130				16,900				
150				20,890				
100	9570	FXFDL150SW/66/50K/BZ-KNC	5000K	13,000	400	1/2" Knuckle	●	P
130				16,900				
150				21,028				

ACCESSORIES (Ordered Separately)



Photocell Kit
K141030 REC3PLK/PHO
(P10141+P10030 Twist lock Photocell and Receptacle Mount 120-277V 3 Prong)



Slip Fitter
P10414 MT-FDL/SF/BZ
(Slip Fitter Mount for #9567,9568)



Surge Protector
P10389 SPD-L-10KV-277
(10KV Surge Protection 120-277V)




P10390 SPD-L-20KV-277
(20KV Surge Protection 120-277V)




DIMENSIONS

150W-Yoke Mount
9.50-lbs




150W-Knuckle Mount
9.30-lbs



PHOTOMETRICS CHART


150 Watt-4000K-Yoke
DLC Premium



Illuminance at a Distance			
	Center Beam fc	Beam Width	
1.7R	3,000 fc	3.2 ft	4.6 ft
3.3R	796 fc	6.2 ft	9.0 ft
5.0R	347 fc	9.3 ft	13.6 ft
6.7R	193 fc	12.5 ft	18.3 ft
8.3R	126 fc	15.5 ft	22.7 ft
10.0R	86.7 fc	18.7 ft	27.3 ft

■ Vert. Spread: 86.1°
■ Horiz. Spread: 107.5°


150 Watt-5000K-Yoke
DLC Premium



Illuminance at a Distance			
	Center Beam fc	Beam Width	
1.7R	3,000 fc	3.2 ft	4.6 ft
3.3R	796 fc	6.2 ft	9.0 ft
5.0R	347 fc	9.3 ft	13.6 ft
6.7R	193 fc	12.5 ft	18.3 ft
8.3R	126 fc	15.5 ft	22.7 ft
10.0R	86.7 fc	18.7 ft	27.3 ft

■ Vert. Spread: 86.1°
■ Horiz. Spread: 107.5°


150 Watt-4000K-Knuckle
DLC Premium



Illuminance at a Distance			
	Center Beam fc	Beam Width	
1.7R	3,000 fc	3.2 ft	4.6 ft
3.3R	796 fc	6.2 ft	9.0 ft
5.0R	347 fc	9.3 ft	13.6 ft
6.7R	193 fc	12.5 ft	18.3 ft
8.3R	126 fc	15.5 ft	22.7 ft
10.0R	86.7 fc	18.7 ft	27.3 ft

■ Vert. Spread: 86.1°
■ Horiz. Spread: 107.5°

150 Watt-5000K-Knuckle
DLC Premium



Illuminance at a Distance			
	Center Beam fc	Beam Width	
1.7R	3,000 fc	3.2 ft	4.6 ft
3.3R	796 fc	6.2 ft	9.0 ft
5.0R	347 fc	9.3 ft	13.6 ft
6.7R	193 fc	12.5 ft	18.3 ft
8.3R	126 fc	15.5 ft	22.7 ft
10.0R	86.7 fc	18.7 ft	27.3 ft

■ Vert. Spread: 86.1°
■ Horiz. Spread: 107.5°

PACKAGE

Case Qty 1 pc

