NOTURALED[®] Product Engineering Spec

_	

Product Spec						
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires					
Item Code	7701					
Stock Code	LED-FXSAL150/30K/BK/3S	PICTURE	THE REAL PROPERTY OF			
Mounting	EA6/SB/SF/WM/Yoke Mount					
Housing Color	Black					

Electric Cha	racteristics	Photometr	Photometric Characteristics		
Rated Wattage (W)	150	Lumen (lm)	20187		
Tested Wattage (W)	152.3	Efficacy (lm/w)	133		
Input Voltage (V)	100~277	CRI	>70		
Voltage Frequency (Hz) 50/60		CCT (K)	3000		
Input Current (A) 1.3		Beam Angle (°)	Туре З		
Power Factor	>0.9	General	General Characteristics		
Replacement Wattage (W)	400~575	Operating Temperature	-40°F~140°F		
Surge protect level	10KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10V	IP rating	IP65		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
Product Di	mensions	Sugges	Suggested Accesory		
Weight (lbs.)	23.6	Phot	Photocell Sensor		
Height (in)	3	Mot	Motion Sensor		
Length (in)	23.2	EA6/SB/	EA6/SB/SF/Yoke Mount		
Width (in)	15	W	Wall Mount		
Mounting Height (ft)		Туре 4	Type 4, Type 5 Lens		
Cable Length (ft)	1.97	48	480V driver		
	Qua	lifications			
UL/ETL	ETL	LM79	V		
Energy Star		LM80	V		
DLC		IES File	V		
CEC		FDA			
JA8		NEMA			
FCC	\checkmark	Dimmer List			
RoHS	V				

Comments: