



Product Spec					
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires				
Item Code	7702]			
Stock Code	LED-FXSAL150/30K/WH/3S	PICTURE			
Mounting	EA6/SB/SF/WM/Yoke Mount	1			
Housing Color	White				

Housing Color	White				
Electric Cha	aracteristics	Photometric	Characteristics		
Rated Wattage (W)	150	Lumen (lm)	20187		
Tested Wattage (W)	152.3	Efficacy (lm/w)	133		
Input Voltage (V)	100~277	CRI	>70		
Voltage Frequency (Hz)	50/60	сст (к)	3000		
Input Current (A)	1.3	Beam Angle (∘)	Type 3		
Power Factor	>0.9	General Ch	General Characteristics		
Replacement Wattage (W)	400~575	Operating Temperature	-40°F~140°F		
Surge protect level	10KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10V	IP rating	IP65		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
Product Dimensions		Suggeste	Suggested Accesory		
Weight (lbs.)	23.6	Photoc	Photocell Sensor		
Height (in)	3	Motio	Motion Sensor		
Length (in)	23.2	EA6/SB/SF/Yoke Mount			
Width (in)	15	Wall	Wall Mount		
		Type 4, Type 5 Lens			
Mounting Height (ft)		3 F - 7	71		
Mounting Height (ft) Cable Length (ft)	1.97		driver		
	1.97				
Cable Length (ft)		480\			
	Qua	480\	/ driver		
Cable Length (ft) UL/ETL Energy Star	Qua	Alifications LM79	√ driver		
Cable Length (ft) UL/ETL Energy Star DLC	Qua	LM79 LM80	√ driver √ √		
Cable Length (ft) UL/ETL Energy Star DLC CEC	Qua	LM79 LM80 IES File	√ driver √ √		
Cable Length (ft) UL/ETL	Qua	LM79 LM80 IES File FDA	√ driver √ √		