Noturaled[®] Product Engineering Spec

CategoryIItem CodeIStock CodeIMountingIHousing ColorIElectric ChRated Wattage (W)Tested Wattage (W)IInput Voltage (V)IVoltage Frequency (Hz)I	Recessed Downlight 9526 LED4RL10-75L9CCT5 recessed White haracteristics 10	PICTURE			
Stock Code	LED4RL10-75L9CCT5 recessed White haracteristics 10	PICTURE			
Mounting Housing Color Electric Ch Rated Wattage (W) Tested Wattage (W) Input Voltage (V)	recessed White haracteristics 10	PICTURE			
Housing Color Electric CH Rated Wattage (W) Tested Wattage (W) Input Voltage (V)	White haracteristics 10	-			
Electric Cl Rated Wattage (W) Tested Wattage (W) Input Voltage (V)	haracteristics 10				
Rated Wattage (W) Tested Wattage (W) Input Voltage (V)	10				
Rated Wattage (W) Tested Wattage (W) Input Voltage (V)	10		-		
Tested Wattage (W) Input Voltage (V)			Photometric Characteristics		
Input Voltage (V)			Lumen (lm)	750	
	10		Efficacy (lm/w)	75	
Voltage Frequency (Hz)	120		CRI	90	
	60		ССТ (К)	2700 / 3000 / 3500 / 4000 / 5000	
Input Current (A)	0.1		Beam Angle (°)	100	
Power Factor	>0.9			Characteristics	
Replacement Wattage (W)	60	Operatir	ng Temperature	5°F~104°F	
Surge protect level	1.5KV	Storag	ge Temperature	14°F~104°F	
Dimmable	Incandescent dimming		IP rating	Wet Location	
THD	-		Rated Life	50000 hrs.	
			Warranty	5 years	
_					
Product	Dimensions		Suggested Accessory		
Weight (lbs.)	0.6				
Height (in)	2.99				
Length (in)	5.09				
Width (in)	5.09				
Mounting Height (ft.)					
Cable Length (ft.)					
	Quali	fications			
UL/ETL	ETL/cETL		LM79	V	
Energy Star	, • √	1	LM80	√	
DLC	·	1	IES File	√	
CEC	V	1	IC Rated	√	
JA8	<u></u>	1	Air-tight Rated	V	
FCC	v V		Dimmer List	v	
RoHS	v V		Diminer List		
Comments:	v	1			