NATL-5096-24-HWD10

24V Class II Dimmable Hardwire LED Driver (0-10V dimming)

Source: 120-277V Input / 24V Output

96W

PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems.

FEATURES

- · 0-10V dimming
- · Conduit access wiring compartment
- · Meet Class II output limits
- · 24V DC rated output
- · Includes 10' power line connector (NALTL-10)
- · cULus listed enclosure & cULus recognized driver

ELECTRICAL

Input Voltage: 120-277V Output Voltage: 24VDC Wattage: 96W THD: <20% Power Factor: 0.95 Dimming: 0-10V

Protection: Short circuit, over voltage and over-temperature protection

COMPATIBLE NORA 24V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NUTP1	24V Standard Tape Light (Silicone Encapsulated)
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NIII R	24V Lighthar Silk SBC

OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector (included) **NALTL-30:** 30' Power Line Connector

NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.


LABELS AND LISTINGS

- · cULus Listed Enclosure
- · cULus Recognized Driver



Type
Project
Catalog No.
Notes

PRODUCT IMAGES & DIMENSIONS



NATL-5096-24-HWD10 24V Class II Dimmable Hardwire LED Driver 0-10V dimming



NALTL-10 / NALTL-30 Power Line Connector (10' included)



NATL-302W Power Line Splitter

24V Class II Dimmable Hardwire LED Driver (0-10V dimming)

Output Voltage / Wattage

NATL-5096-24-HWD10 = 24V Ouput / 96W

Optional Accessories

Description

NALTL-10 = 10' Power Line Connector (included w/each driver)

NALTL-30 = 30' Power Line Connector **NATL-302W** = Power Line Splitter, White

Example: NATL-5096-24-HWD10 = 24V 96W Class II Dimmable Hardwire LED Driver (0-10V dimming)

