

NATL-524 / NATL-545 / NATL-596

24V Plug-In LED Driver

Source: 120V Input / 24V Output
24W, 45W or 96W

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

24V plug-in driver to be used with Nora Lighting's 24 Volt systems.

FEATURES

- Direct connection to a wall outlet
- Non-dimmable
- 24V DC rated output
- Includes power line connector
- cULus listed

ELECTRICAL

Input Voltage: 120V

Output Voltage: 24VDC

Wattage: 24W (NATL-524), 45W (NATL-545) or 96W (NATL-596)

Dimming: Non-Dimmable

CORD LENGTHS

NATL-524W 6" power line connector

NATL-545W 6" power line connector

NATL-524CPW 50" cord and plug / 60" power line connector

NATL-596W 55" cord and plug / 44" power line connector

COMPATIBLE NORA 24V SYSTEMS

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NUTP1	24V Standard Tape Light (Silicone Encapsulated)
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

OPTIONAL ACCESSORY

NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

cULus Listed



PRODUCT IMAGES & DIMENSIONS



NATL-524W / NATL-545W
24V Plug-In LED Driver



NATL-545CPW / NATL-596W
24V Plug-In LED Driver



NATL-302W
Power Line Splitter

24V Plug-In LED Driver

Output Voltage / Wattage

NATL-524W = 24V Output / 24W

NATL-545CPW = 24V Output / 45W

NATL-545W = 24V Output / 45W

NATL-596W = 24V Output / 96W

Optional Accessory

Description

NATL-302W = Power Line Splitter, White

Example: **NATL-596W** = 24V 96W Plug-In LED Driver