# NATLED-5040HW / NATLED-5075HW

24V Constant Voltage Dimmable Hardwire Electronic Driver

# Source: 120V Input / 24V Output

40W or 75W

## PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems.

# FEATURES

- Constant Voltage electronic driver
  Triac or FLV dimming
- Triac or ELV dimming
- Conduit access wiring compartment
  Meet Class II output limits
- 24V DC rated output
- Includes 10' power line connector (NALTL-10)
- cULus listed enclosure & cULus recognized driver

#### ELECTRICAL

Input Voltage: 120V Output Voltage: 24VDC Wattage: 40W (NATLED-5040HW) or 75W (NATLED-5075HW) Load: Operates loads up to 80% for best performance Dimming: Triac or ELV Protection: Short circuit, over voltage and over-temperature protection

### **COMPATIBLE NORA 24V SYSTEMS**

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NUTP1	24V Standard Tape Light (Silicone Encapsulated)
NUTP3	24V RGB Color Changing Tape Light
NUTP5	24V Hy-Brite Tape Light
NUTP7	24V Standard Tape Light (Non-Encapsulated)
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP11	24V RGBW Color Changing Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

## **OPTIONAL ACCESSORIES**

NALTL-10: 10' Power Line Connector (included) NALTL-30: 30' Power Line Connector NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

#### LABELS AND LISTINGS

- cULus Listed
- FCC compliant




Туре

Project

Catalog No.

Notes

## **PRODUCT IMAGES & DIMENSIONS**



NATLED-5040HW / NATLED-5075HW 24V Constant Voltage Dimmable Hardwire Electronic Driver



**NALTL-10 / NALTL-30** Power Line Connector (10' included)



NATL-302W Power Line Splitter

24V Constant Voltage Dimmable Hardwire Electronic Driver	Optional Accessories
Output Voltage / Wattage	Description
NATLED-5040HW = 24V Ouput / 40W NATLED-5075HW = 24V Ouput / 75W	NALTL-10 = 10' Power Line Connector (included w/each driver) NALTL-30 = 30' Power Line Connector NATL-302W = Power Line Splitter, White

Example: NATLED-5075W = 24V 75W Constant Voltage Dimmable Hardwire Electronic Driver

NORA