

# NMPK Series

12V LED Puck Light

Source: 2.4W LED  
210lm

Type

Project

Catalog No.

Notes

## PRODUCT DESCRIPTION

Nora Lighting introduces a new slim light disk LED system for accent, under cabinet, cove lighting and jewelry cases, and other applications with limited space. These low-profile fixtures can be chained together to provide excellent and even illumination on all surfaces. Light disk is one of the most energy efficient products in the market. Combined with ultra low-profile housing, Nora's light disk offers unique features and a great ease of installation. LED technology eliminates forward heat from the fixture, also no UV or infrared rays to harm artwork, retail displays or heat sensitive foods.

## FEATURES

- LEDs produce 210 lumens (70 lumens per watt)
- Ten lights can be daisy-chained up to 90' away from driver
- 3000K or 4200K
- Bronze, Chrome or White finish
- Well suited for very small spaces: 1/2" deep with 2-3/4" diameter
- Easy installation using one screw
- 3", 6", 12" and 24" interconnection cables included with each puck
- Dimmable with Magnetic Power Supply
- cETLus listed for dry locations
- 30,000 hours of rated lamp life

**Included with each LED Puck:** (1) Mounting Clip and Screw, (1) 3" Interconnection Cable [NAPK-702], (1) 6" Interconnection Cable [NAPK-706], (1) 12" Interconnection Cable [NAPK-712], (1) 24" Interconnection Cable [NAPK-724] and (1) Mini Coupler [NAPK-713]

## ELECTRICAL

**Input:** 12VDC

**Lumens / Wattage:** 210lm / 4.2W

**Color Temperature:** 3000K or 4200K

**Max Run Length:** 10.7' (w/ NMT-60/12C2) or 14.2" (w/ NAPK-560HW/12)


**Dimming:** Dimmable with Magnetic Power Supply

## LABELS AND LISTINGS

- cULus Listed for Dry Location
- 3-Year Limited Warranty
- RoHS compliant



## PRODUCT IMAGES AND DIMENSIONS



## NMPK LED Puck Light

Description	12V LED Drivers	Driver Accessories	Accessories			
			Connectors	Power Feed	Others	Finish
NMPK1-3LED30C = 3000K / Chrome Finish	NMTD-40/12D	NALTL-10	NAPK-702 NAPK-703 NAPK-706 NAPK-712 NAPK-724 NAPK-736 NAPK-748	NAPK-709 NAPK-711	NAPK-701 NAPK-713 NMPKA-RECW NMPKA-RECBZ NMPKA-RECC NATL-415	B = Black W = White
NMPK1-3LED42BZ = 4200K / Bronze Finish	NMTD-60/12D	NALTL-30				
NMPK1-3LED42C = 4200K / Chrome Finish	NAPK-5030HW/12	NATL-302W				
NMPK1-3LED42W = 4200K / White Finish	NAPK-5060HW/12					
	NAPKED-5040HW					
	NAPKED-5060HW					
	NMT-244/12C2D1					
	NMT-244/12C2D2					
	NATL-5060-12-HWD10					

**Example:** NMPK1-3LED30W / NMTD-60/12D / NALTL-30 / NAPK-702W

# NMPK Series

12V LED Puck Light  
Accessories

Type
Project
Catalog No.
Notes



Splitter

**NAPK-701B** Black  
**NAPK-701W** White  
To separate 4 puck light runs from a single driver or to split a run between puck lights. One in and four out.



Interconnection Cable

**NAPK-702** 2" Cable  
**NAPK-703** 3" Cable  
**NAPK-706** 6" Cable  
**NAPK-712** 12" Cable  
**NAPK-724** 24" Cable  
**NAPK-736** 36" Cable  
**NAPK-748** 48" Cable  
Finish: Black (B), White (W)  
Allows easy linking of two pucks.



Mini Coupler

**NAPK-713B** Black  
**NAPK-713W** White  
Used to connect two interconnection cables together or to add interconnection cable to power line interconnector.  
Dim.: 3/8" W; 3/4" L; 1/4" H



Power Line Interconnector

**NAPK-711B** 12" black w/switch  
**NAPK-711W** 12" white w/switch  
**NAPK-709B** 18" black  
**NAPK-709W** 18" white  
Connects puck light to a driver.



Recessed Housing Accessory

**NMPKA-RECBZ** Bronze  
**NMPKA-RECC** Chrome  
**NMPKA-RECW** White  
Used to mount puck light recessed and flush



2' Wire Raceway

**NATL-422B** Black  
**NATL-422W** White  
Field-cutable plastic. Includes wire channel with double faced tape and cover.



Power Line Connector

**NALTL-10** 10' Cable  
**NALTL-30** 30' Cable  
For use with Class II drivers. Carries output from driver, requires power line cable.  
5" Power Line Splitter  
**NATL-302W**



Low Voltage Splice Box

**NATL-415W**  
Use to join low voltage lead to low voltage power line connector or interconnector.



Direct Plug-In LED Driver

**NAPK-524/12** Black 24W  
**NAPK-524W/12** White 24W  
**NAPK-550/12** Black 50W  
Voltage: 120V/12V  
Wattage: 24W or 50W  
Dimming: Non-Dimmable  
Cable Length: 4' cord & plug and 60" power line connector for NAPK-550/12



Class II Hardwire LED Driver with Regulator, MLV Dimming  
**NMTD-40/12D** 40W  
**NMTD-60/12D** 60W  
Voltage: 120-277V/12V  
Wattage: 40W or 60W  
Dimming: Magnetic Low Voltage  
Regulator: Integral regulator for constant current and voltage  
Includes: 10' Power Line Connector



Class II Hardwire LED Driver Non-Dimmable  
**NAPK-5030HW/12** 30W  
**NAPK-5060HW/12** 60W  
Voltage: 120-240V/12V  
Wattage: 30W or 60W  
Dimming: Non-Dimmable  
Includes: 10' Power Line Connector



Class II Hardwire LED Driver ELV Dimming  
**NAPKED-5040HW** 12V 40W  
**NAPKED-5060HW** 12V 60W  
Input Voltage: 120V  
Dimming: Electronic Low Voltage  
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming  
**NMT-244/12C2D1** 120/12V 240W  
**NMT-244/12C2D2** 277/12V 240W  
Input Voltage: 120V or 277V  
Dimming: Magnetic Low Voltage  
Wattage: (4) 60W  
Includes: (4) 10' Power Line Connectors



Class II Hardwire LED Driver 0-10V Dimming  
**NATL-5060-12-HWD10** 60W  
Voltage: 120-277V/12V  
Wattage: 60W  
Dimming: 0-10V  
Includes: 10' Power Line Connector