NRS17-301

Nepro Wall Wash

Lamp: (1) 150W 120V T type Halogen lamp (150W included)

PRODUCT DESCRIPTION

Line voltage linear halogen wall wash luminaire.

SPECIFICATION

HOUSING

0.07" die-cast aluminum housing. Lamp Containment Barrier - Heat resistant glass, frosted lamp shield, min 0.12" thick, overall 5-3/8" long by 1-1/8" wide; mechanically secured to lampholder by metal clips.

ELECTRICAL WIRING

Size: 18 Gauge AWG 200°C, 300V

SOCKET

R7S base rated for 250V, 150W max.; secured to enclosure by corrosion protected or resistant metal brackets.

UNIVERSAL CONNECTOR

Construction: 0.07" die cast aluminum shell Contacts: Copper for positive and neutral Copper contact spring on top to provide solid contact with ground conductor located on top of rail.

FINISHES

Brushed Nickel and Bronze are available.

LABELS AND LISTINGS

cULus Listed for dry location only.

ENORALIGHTING.


Туре

Project

Catalog No.

Lamp/Wattage

DIMENSIONS



Height : 4-5/16" Width : 2-1/4" Length : 7-1/2" Max. Extension : 7-1/2"



Nepro Wall Wash Catalog No. Finish NRS17-301 BN = Brushed Nickle BZ = Bronze S = Silver

Create a complete item number: Example: NRS17-301BN



6505 Gayhart St., Commerce, CA 90040 • Phone: 800.686.6672 • FAX: 800.500.9955 • www.noralighting.com e-mail: nora@noralighting.com • Specifications subject to change without notice. © 2014