PRODUCT DESCRIPTION

Universal die-cast aluminum lamp holder accepts LED and line voltage lamps. Contemporary track head accepts a range of lamps from PAR20 to PAR38.

FEATURES

- · Retractable socket hides lamp's neck
- Ultra clean appearance
- $\cdot\,$ Heat resistant teflon coated wire lead
- \cdot Low profile mounting / adjustment arm
- · High strength stainless steel electrical contacts
- · One or two circuit track capable.

CONSTRUCTION

Body Assembly: 0.03" Drawn steel cup contains an adjustable socket for shielding the base and neck of any lamp source.

Adjustable Arm: 0.080" Rigid steel bracket connects fixture housing to electrical contact head. Single screw locks vertical angle of fixture.

ELECTRICAL

Voltage: 120V input Socket: Medium base Lamp: R/PAR20, BR/PAR30 or PAR38 (not included) Wattage: 100W max.

FINISH

Available in black and white finishes.

ONE/TWO CIRCUIT CONVERSION

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.

LABELS AND LISTINGS

cULus Listed for dry locations



.


Type Project


Catalog No.

Notes

PRODUCT IMAGES AND DIMENSIONS







Universal™ Flatback Lamp Holder			
Cotolog No.	Finiah	Adaptar Ctula	

Catalog No.	Finish	Adapter Style
NTH-139	B = Black	(blank) = H-style
	W = White	/J = J-style
		/L = L-style

Example: NTH-139B = Universal™ Flatback Lamp Holder, Black Finish, H-Style Adapter	

