NTH-910

Architectural Track Head Cylinder with Baffle Source: 50W max.

MR16 GU10 (not included)

PRODUCT DESCRIPTION

Constructed of die-cast and extruded aluminum, the architectural cylinder is minimal in design. A die-cast baffle helps shield aperture brightness.

FEATURES

- Die-cast aluminum provides superior strength and rigidity
- Baffle eliminates glare
- . One or Two-Circuit track capable

SPECIFICATION

Construction: Extruded aluminum construction with simple, cylindrical design. All edges are sharp and clean.

Structural Arm: Extruded 0.055" aluminum arm connects fixture housing to electrical contacts. Internal tightening mechanism maintains desired lamp aiming angles. Structural arm also functions as wire way, completely concealing lead wire from socket to contact head.

Baffle: 0.085" die-cast aluminum baffle, provides finished appearance and assists in eliminating glare from housing interior.

ELECTRICAL

Socket: Porcelain twist and lock GU10 socket Wattage: 50W maximum Lamp: MR16

One/Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

Finishes: Black, white and silver finishes are available; contact warehouse for custom finishes.

LISTING

cULus Listed for Dry Locations






Project

Catalog No.

Notes

PRODUCT IMAGES & DIMENSIONS





NTH-910R Black Finish with Black Baffle



NTH-910S Silver Finish with SilverBaffle



NTH-910W White Finish with White Baffle

Architectural Track Head Cylinder with Baffle

Series	Finish
NTH-910 = Architectural Track Head Cylinder with Baffle	B = Black with Black Baffle
	S = Silver with Silver Baffle
	W - White with White Baffle

White with White Baffle

Example: NTH-910W = Architectural Track Head Cylinder, White finish and White Baffle

