OCIOCI APOLLO® AG CIRCLINE

OWLED

Features and Specifications

Applications

Ideal for retrofitting existing fluorescent OW fluorescent fixtures, CFL's and incandescents in hog barns, poultry barns and tie-stall barns.

Constructed

All fixture types include acrylic lens, [2] wire nuts, [2] lock nuts, driver plate, and mounting plate bracket. Driver plate is vented for thermal management. Components for hardwired fixtures include polycarbonate flat base and cork gasket. Jelly jar comes with a screw-in base.

Certification & Listing

· UL Listed.

Electrical Available in 120-277v.

Rated Life 50,000 hours.

Warranty

Orion LED fixtures are covered by a five-year limited warranty. Accessories and individual components are covered by separate OEM supplier warranties.



Required Ordering Information

1 Select				
Series				
OWLED	White Circuline LED AG Unit			

2 Select						
Base Type						
(blank)	Jelly Jar					
HW	Hardwired					

3 Select						
Color Temperature						
5K	5000°K					

Options



HW = Hardwired Back of Fixture Shown



Jelly Jar Back of Fixture Shown



Offor Apollo® AG CIRCLINE

Physical and Performance Information¹

OWLED

Series	Input Voltage	Input Power	Input Current	Power Factor	Light Output	ССТ	CRI
OWLED	120-277v	29w	0.241-0.104 A	≥ .99	2200 lm	5000°K	<u>></u> 75

Additional Specification Information

 $^{^{\}rm 1}$ Actual performance may vary by up to $\pm 10\%$ of values listed.