

| Product Information | | | | | | | Physical Information | | Photometric Characteristics | | | | |
|--|---------|------|-------|--|-------------|-----------|----------------------|----------|-----------------------------|--------------|---------------------|-----------------|--------------|
| Watts | Bulb | Base | Item# | Description | Voltage (V) | Case Qty. | Dia (in) | MOL (in) | Beam Angle | Spread | Initial Lumens (lm) | Avg. Life (Hrs) | UPC |
| PAR30 Long Neck Series - Medium Screw Base | | | | | | | | | | | | | |
| 50 | PAR30LN | E26 | 3026 | *50PAR30LN/SP/120 | 120 | 15 | 4.5 | 3.74 | 10° | Spot | 660 | 2500 | 844366030260 |
| 50 | PAR30LN | E26 | 3084 | *50PAR30LN/NFL/120 | 120 | 15 | 4.5 | 3.74 | 25° | Narrow Flood | 660 | 2500 | 844366030840 |
| 50 | PAR30LN | E26 | 3027 | *50PAR30LN/FL/120 | 120 | 15 | 4.5 | 3.74 | 40° | Flood | 660 | 2500 | 844366030277 |
| 50 | PAR30LN | E26 | 3028 | *50PAR30LN/SP/130 @ 120 volts a pproximate 44 watts, 500 lumens, 5000 hours | 130 | 15 | 4.5 | 3.74 | 10° | Spot | 660 | 2500 | 844366030284 |
| 50 | PAR30LN | E26 | 3085 | *50PAR30LN/NFL/130 @ 120 volts a pproximate 44 watts, 500 lumens, 5000 hours | 130 | 15 | 4.5 | 3.74 | 25° | Narrow Flood | 660 | 2500 | 844366030857 |
| 50 | PAR30LN | E26 | 3029 | *50PAR30LN/FL/130 @ 120 volts a pproximate 44 watts, 500 lumens, 5000 hours | 130 | 15 | 4.5 | 3.74 | 40° | Flood | 660 | 2500 | 844366030291 |
| 75 | PAR30LN | E26 | 3030 | *75PAR30LN/SP/120 | 120 | 15 | 4.5 | 3.74 | 10° | Spot | 1100 | 2500 | 844366030307 |
| 75 | PAR30LN | E26 | 3086 | *75PAR30LN/NFL/120 | 120 | 15 | 4.5 | 3.74 | 25° | Narrow Flood | 1100 | 2500 | 844366030864 |
| 75 | PAR30LN | E26 | 3031 | *75PAR30LN/FL/120 | 120 | 15 | 4.5 | 3.74 | 40° | Flood | 1100 | 2500 | 844366030314 |
| 75 | PAR30LN | E26 | 3032 | *75PAR30LN/SP/130 @ 120 volts a pproximate 66 watts, 1100 lumens, 5000 hours | 130 | 15 | 4.5 | 3.74 | 10° | Spot | 1100 | 2500 | 844366030321 |
| 75 | PAR30LN | E26 | 3087 | *75PAR30LN/NFL/130 @ 120 volts a pproximate 66 watts, 1100 lumens, 5000 hours | 130 | 15 | 4.5 | 3.74 | 25° | Narrow Flood | 1100 | 2500 | 844366030871 |
| 75 | PAR30LN | E26 | 3033 | *75PAR30LN/FL/130 @ 120 volts a pproximate 66 watts, 1100 lumens, 5000 hours | 130 | 15 | 4.5 | 3.74 | 40° | Flood | 1100 | 2500 | 844366030338 |

*Items only available for special orders

HALOGEN

CFL

FL

BALLAST

GERMICIDAL