

Product Information							Physical Information		Photometric Characteristics				UPC
Watts	Bulb	Base	Item#	Description	Voltage (V)	Case Qty.	Dia (in)	MOL (in)	Beam Angle	Spread	Initial Lumens (lm)	Avg. Life (Hrs)	UPC
PAR38 Series - Medium Screw Base													
90	PAR38	E26	3078	*90PAR38/NSP/120	120	15	5.32	4.76	9°	Narrow Spot	1270	2500	844366030789
90	PAR38	E26	3048	*90PAR38/SP/120	120	15	5.32	4.76	12°	Spot	1270	2500	844366030482
90	PAR38	E26	3049	*90PAR38/FL/120	120	15	5.32	4.76	30°	Flood	1270	2500	844366030499
90	PAR38	E26	3050	*90PAR38/WFL/120	120	15	5.32	4.76	50°	Wide Flood	1270	2500	844366030505
90	PAR38	E26	3079	*90PAR38/NSP/130	130	15	5.32	4.76	9°	Narrow Spot	1270	2500	844366030796
				@ 120 volts a pproximate 79 watts, 1000 lumens, 5000 hours									
90	PAR38	E26	3051	*90PAR38/SP/130	130	15	5.32	4.76	12°	Spot	1270	2500	844366030512
				@ 120 volts a pproximate 79 watts, 1000 lumens, 5000 hours									
90	PAR38	E26	3052	*90PAR38/FL/130	130	15	5.32	4.76	30°	Flood	1270	2500	844366030529
				@ 120 volts a pproximate 79 watts, 1000 lumens, 5000 hours									
90	PAR38	E26	3053	*90PAR38/WFL/130	130	15	5.32	4.76	50°	Wide Flood	1270	2500	844366030536
				@ 120 volts a pproximate 79 watts, 1000 lumens, 5000 hours									

*Items only available for special orders

HI

HALOGEN

CFL

FL

BALLAST

GERMICIDAL