PREMISE

Performance Value High Bays

100W / 150W / 200W / 240W

100-277V & 120-347V

4000K & 5000K

HBV1-Series LED Monopoint High Bays



The HBV1-Series is a monopoint high bay offering that combines performance and price to give you the best of both worlds.

With an efficacy of 150 lm/W, they are the perfect choice for applications where an economical solution is required.

Key Features & Benefits

- Up to 150 lumens/W
- Offered in our most popular wattages: 100W, 150W, 200W, and 240W
- Available in both 100-277V or 120-347V with 1-10V dimming
- Includes a fixture hook with setscrew and 6-foot cord for easy installation

- IP65 rated for protection against water jet spray
- A native 110° beam angle works well with mid to high ceiling applications
- Aluminum and Prismatic 90° Reflectors available as additional accessories

WHY CHOOSE THIS FIXTURE?

FIXTURE HOOK MOUNTING

Included fixture hook with setscrew prevents vibratory loosening when chain hanging (additional Carabiner accessory available as an option)

IP65 RATED ······

Provides protection against water jets from any angle


REFLECTOR ACCESSORIES

90° beam angle aluminum and prismatic reflectors available



LOW PROFILE & LIGHTWEIGHT

For improved thermal performance and easy installation



HIGH PERFORMANCE LEDs

High output SMD 2835 LED chips for brighter, more efficient lighting

| 100-277V Models | | | | | | | | | | | |
|-----------------|----------|---------|-----------|-----|-------|----------------------------------|---------|--|--|--|--|
| MODEL# | VOLTAGE | WATTAGE | LUMEN | CRI | ССТ | OPERATION RANGE | DIMMING | | | | |
| HBV1-1004-1 | 100-277V | 100W | 14,331 lm | 80 | 4000K | -40°F to +122°F / -40°C to +50°C | 1-10V | | | | |
| HBV1-1005-1 | | 100W | 14,539 lm | | 5000K | | | | | | |
| HBV1-1504-1 | | 150W | 21,791 lm | | 4000K | | | | | | |
| HBV1-1505-1 | | 150W | 22,030 lm | | 5000K | | | | | | |
| HBV1-2004-1 | | 200W | 29,500 lm | | 4000K | | | | | | |
| HBV1-2005-1 | | 200W | 29,912 lm | | 5000K | | | | | | |
| HBV1-2404-1 | | 240W | 34,986 lm | | 4000K | | | | | | |
| HBV1-2405-1 | | 240W | 35,487 lm | | 5000K | | | | | | |

| 120-347V Models | | | | | | | | | | | |
|-----------------------|----------|---|---|-----|-------|----------------------------------|---------|--|--|--|--|
| MODEL# | VOLTAGE | WATTAGE | LUMEN | CRI | ССТ | OPERATION RANGE | DIMMING | | | | |
| HBV1-1004-3 | 120-347V | 100W | 14,953 lm | 80 | 4000K | -40°F to +122°F / -40°C to +50°C | 1-10V | | | | |
| HBV1-1005-3 | | 100W | 15,169 lm | | 5000K | | | | | | |
| HBV1-1504-3 | | 150W | 22,089 lm | | 4000K | | | | | | |
| HBV1-1505-3 | | 150W | 22,332 lm | | 5000K | | | | | | |
| HBV1-2004-3 | | 200W | 29,749 lm | | 4000K | | | | | | |
| HBV1-2005-3 | | 200W | 30,119 lm | | 5000K | | | | | | |
| HBV1-2404-3 | | 240W | 35,864 lm | | 4000K | | | | | | |
| HBV1-2405-3 | | 240W | 36,295 lm | | 5000K | | | | | | |
| Available Accessories | | | | | | | | | | | |
| MOD | EL# | DESCRIPTION | | | | | | | | | |
| HBV-REF1-AL-90 | | | 90 degree aluminum reflector for HBV1 High Bays 100W / 150W models | | | | | | | | |
| HBV-REF2-AL-90 | | | 90 degree aluminum reflector for HBV1 High Bays 200W / 240W models | | | | | | | | |
| HBV-REF1-PC-90 | | | 90 degree prismatic reflector for HBV1 High Bays 100W / 150W models | | | | | | | | |
| HBV-REF2-PC-90 | | 90 degree prismatic reflector for HBV1 High Bays 200W / 240W models | | | | | | | | | |
| HB-CARABINER | | Carabiner for suspending HBV1 High Bays | | | | | | | | | |